

Datasheet



ENSTO CLAMPO PRO ENSTO

Tapping connector Y/G, Al/Cu 35-240 mm²

REF. KE69.3 | 1933085 | EAN. 6418677192050

Tapping block, yellow/green, Al/Cu 35-240 mm²

> [Visit e-catalogue](#)

Main description:

Tapping block, yellow/green, Al/Cu 35-240 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 - 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	15 - 185 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	35 - 185 mm ²
Connectable conductor cross section multi-wired (Min-Max)	35 - 240 mm ²
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	4
Mounting method	Direct mounting

Material insulation body	Thermoplastic
Operating temperature (Min-Max)	-5 - 80 °C
Width	64 mm
Height	67 mm
Depth	130 mm
Explosion-tested version 'Ex e'	No
Colour	Green/yellow
Inflammability class of insulation material according to UL 94	V2

Documentation

Technical documentation

IG_Clampo Pro.pdf | PDF (0.51Mo)

CAD & Design specs / BIM

DD_KE269.pdf | PDF (0.19Mo)

2D_KE269.dwg | DWG (0.27Mo)

 3D_KE69_PK2_V1.stp | IFC (6.79Mo) 2D_KE269_2.dxf | DXF (0.99Mo)

Agreements & certificates

 CE_KE69_2024_EN.pdf | PDF (0.05Mo) CE_KE69_2024_FI.pdf | PDF (0.05Mo) LGRP-02011-V01.01-EN.pdf | PDF (0.78Mo)