

PU (SPU): 500 (50) Piece

-

500

+

Add to project

- Data sheet as PDF
- Compare
- Bookmark
- Find distributors

Overview

Data

Approval

Downloads

Related products

Customers also purchased



Product details

Details ^

Electrical data

Rated voltage EN (Ex e II) 550 V

Ratings per IEC/EN 60664-1

Rated current 24 A

Connection data

Connection technology PUSH WIRE®

Actuation type Push-in

Connectable conductor materials Copper

Solid conductor 0.75 ... 2.5 mm² / 18 ... 14 AWG

Strip length 12 mm / 0.47 Inch

Geometrical Data

Width 24 mm / 0.945 inch

Height 13.1 mm / 0.516 inch

Depth 19.5 mm / 0.768 inch

Material Data

Color light gray

Cover color light gray

Flammability class per UL94 V2

^ Load 0.101 MJ

^ 4 700 ~

Item no. 773-498



Environmental Requirements

Surrounding air (operating) temperature

60 °C

Continuous operating temperature up to

105 °C



Commercial data

Country of Origin

DE

GTIN

4044918764865

Product Group

7 (Push Wire Conn.)



Approvals / CertiTcates

Ex-Approvals ^

Logo
Approval
CertiTcate name

Logo



Approval:

ATEX

UL International Demko A/S

CertiTcate name:

DEMKO 03 ATEX 131845U (II 2 G Ex eIIC Gb)

English

PDF (866.3 kB)

› **Download**

› **Bookmark**

UL-Approvals ^



Downloads



entation ^

Item no. 773-498



773-498
Oct 19, 2017



DOC
25.6 kB

 German

- › Download
- › Bookmark

CAD Tles 



Compatible products

Mounting adapter 

 Show fewer  Show more

› United States (EN)

› We are happy to help

 1-800-DIN-RAIL (346-7245)



© 2018 WAGO Corporation

Item no. 773-498

Careers



[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)