



PU (SPU): 1 Piece

-

1

+

Add to project

Data sheet as PDF

Compare

Bookmark

Find distributors

Overview

Data

Approval

Downloads

Related products

Customers also purchased

Description

Note on Continuous Service Temperature:

-35°C ... +85°C

PVC cable for temperatures = 70 °C (including halogen-free)

Insulating parts for temperatures = 105 °C

Only in mated condition with strain relief housing (These compact connectors are not designed for use in open, easily accessible areas)



Product details

Details ^

Electrical data

Ratings per IEC/EN 60664-1

| | |
|---------------------------------|---|
| Rated voltage (III / 3) | 400 V |
| Rated impulse voltage (III / 3) | 6 kV |
| Rated current | 16 A |
| Legend (ratings) | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

Connection data

| | |
|----------|------------------|
| length | 9 mm / 0.35 Inch |
| of poles | 5 |

Item no. 771-9995/207-202



Ground function

with preceding GND contact

Conductor preparation

tip-bonded

— Geometrical Data

Pin spacing 10 mm (0.394 inch)

Total length 2 m

— Mechanical data

Coding A

Mating force of a plug-in connection approx. 20 ... 70 N (depending on pole number)

Retention force of a plug-in connection when locked: > 80N

Unmating force of a plug-in connection when unlocked: approx. 20 ... 70 N (depending on pole number)

Connection type cable/adaptor 1 1 Plug

— Plug connection

Mismating protection Yes

Locking of plug-in connection locking lever

Locking lever no

— Material Data

Color white

Insulating material Polyamide 66 (PA 66)

Flammability class per UL94 V0

Reaction to fire class per EN 50575 E_{ca}

Contact material Copper or copper alloy, surface-treated

— Environmental Requirements



Item no. 771-9995/207-202



| | |
|---|----------------|
| Surrounding air (operating) temperature | -35 ... 85 °C |
| Processing temperature | -5°C ... +40°C |
| Continuous operating temperature from | -35 °C |
| Continuous operating temperature up to | 85 °C |

Commercial data

| | |
|-------------------|---------------|
| Country of Origin | DE |
| GTIN | 4044918275729 |
| Product Group | 20 (WINSTA) |



Approvals / Certificates

Country specific Approvals ^

Logo
Approval
Certificate name

Logo

CCA

Approval:
CCA
DEKRA Certification B.V.
Certificate name:
NTR NL-7355

 English

PDF (2.6 MB)
› **Download**
› **Bookmark**

Logo

KEMA
UR

Approval:
/KEUR

Item no. 771-9995/207-202



English

PDF (2.7 MB)

- › **Download**
- › **Bookmark**



Downloads

Documentation ^

Bid Text

771-9995/207-202
WINSTA MIDI 5-polig
Jan 25, 2016



DOC
26.1 kB

 German

- › **Download**
- › **Bookmark**



Compatible products

Locking lever ^

^ Show fewer v Show more

Marking accessories v

protection v



Item no. 771-9995/207-202

Product family



WINSTA MIDI

> Show all products from the family.

> United States (EN)

> We are happy to help

 **1-800-DIN-RAIL (346-7245)**



Item no. 771-9995/207-202



© 2018 WAGO Corporation

[Contact](#)

[Careers](#)

[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)