

**Availability** ✓

PU (SPU): 25 Piece



Add to project

Data sheet as PDF

Compare

Bookmark

Find distributors

**Overview****Data****Downloads****Related products****Customers also purchased****Family**

# Description

## Note on Continuous Service Temperature:

-35°C to +85°C

Insulating parts for temperatures = 105°C



## Product details

### Details ^

#### — Connection data

No. of poles	4
Connectable sheathed cable diameter	9 ... 13 mm

#### — Geometrical Data

Width	44.6 mm / 1.756 inch
Height	17 mm / 0.669 inch
Depth	50 mm / 1.969 inch

#### — Mechanical data

Degree of protection	IP20
----------------------	------

#### — Material Data



black

Material

Polyamide 66 (PA 66)

**Item no. 770-504**



Wire load

0.326 MJ

Weight

11.8 g

## – Environmental Requirements

Surrounding air (operating) temperature	-35 ... 85 °C
Processing temperature	-5°C ... +40°C
Continuous operating temperature from	-35 °C
Continuous operating temperature up to	85 °C

## – Commercial data

Country of Origin	DE
GTIN	4017332755313
Product Group	20 (WINSTA)



**Item no. 770-504**





## Downloads

### Documentation ^

#### Bid Text

770-504  
WINSTA MIDI 4-polig  
Feb 8, 2016



DOC  
24.1 kB

German

- › [Download](#)
- › [Bookmark](#)

### CAD Tles ^



#### Compatible products

### Marking accessories ^

<sup>^</sup> [Show fewer](#) <sup>^</sup> [Show more](#)



#### Product family



**Item no. 770-504**



› Show all products from the family.

› United States (EN)

› We are happy to help

📞 1-800-DIN-RAIL (346-7245)



**Item no. 770-504**



© 2018 WAGO Corporation

[Contact](#)

[Careers](#)

[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)

**Item no. 770-504**