

Availability ✓

PU (SPU): 100 Piece



Add to project

- Data sheet as PDF
- Compare
- Bookmark
- Find distributors

Overview

Data

Approval

Downloads

Related products

Customers also purchased



Product details

Details ^

Electrical data

Rated voltage EN (Ex e II)	550 V
Rated current (Ex e II)	22 A
Rated current (Ex e II) with jumper	20 A

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	800 V
Rated impulse voltage (III / 3)	8 kV
Rated current	24 A
Rated current (2)	32 A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3

Approvals per UL 1059


Rated voltage UL (Use Group B)	600 V
Rated current UL (Use Group B)	20 A
Rated voltage UL (Use Group C)	600 V
Rated current UL (Use Group C)	20 A

Approvals per CSA

Rated voltage CSA (Use Group B)	600 V
Rated current CSA (Use Group B)	20 A

Item no. 2002-1301

Rated current CSA (Use Group C)	20 A
---------------------------------	------



Connection data

Connection technology	Push-in CAGE CLAMP®
Actuation type	Open Tool Slot
Connectable conductor materials	Copper
Nominal cross section	2.5 mm²
Solid conductor	0.25 ... 4 mm² / 22 ... 12 AWG

Geometrical Data

Width	5.2 mm / 0.205 inch
Height from upper-edge of DIN-35 rail	32.9 mm / 1.295 inch
Depth	59.2 mm / 2.33 inch

Mechanical data

Design	horizontal
Type of mounting	DIN-35 rail
Marking level	Center/side marking

Material Data

Color	gray
Insulating material	Polyamide 66 (PA 66)
Fire load	0.104 MJ
Weight	6.07 g

Commercial data

Country of Origin	DE
	4017332999229
Product Group	22 (TOPJOB S)

Item no. 2002-1301





Ex-Approvals ^

Logo
Approval
CertiTcate name

Logo



Approval:

AEx

UL International Germany GmbH c/o Physikalisch Technische Bundesanstalt

CertiTcate name:

E185892 sec.7

 English

PDF (535.0 kB)

› **Download**

› **Bookmark**

Logo



Approval:

ATEX

Physikalisch Technische Bundesanstalt (PTB)

CertiTcate name:

PTB 03 ATEX 1162 U (II 2 G/D Ex e II bzw. I M 2 Ex e I)

Logo



Approval:

IECEEx

Physikalisch Technische Bundesanstalt

CertiTcate name:

IECEEx PTB 03.0004U

 English

PDF (1.9 MB)

› **Download**

› **Bookmark**



speciTc Approvals ^

Item no. 2002-1301





Downloads

Documentation

 Bid Text

2002-1301
Reihenklemmen, TOPJOB S
Aug 13, 2018

DOCX
15.1 kB

 German

- › Download
- › Bookmark

CAD Tles



Compatible products

Carrier rail

 Show fewer  Show more

End plate

 accessories 

Item no. 2002-1301

Marking accessories ▾

Protective Warning Marker ▾

check ▾

ferrule ▾

plug ▾

tools ▾



Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

> Show all products from the family.

United States (EN)



Item no. 2002-1301



> We are happy to help

 **1-800-DIN-RAIL (346-7245)**



© 2018 WAGO Corporation

[Contact](#)

[Careers](#)

[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)