



TOPJOB® S

>

TOPJOB®S feedthrough terminal block; rail mount;
2-conductor; 7.5 mm wide; blue

Price and availability after [Login](#)

Availability

✓

PU (SPU): 50 Piece

-

50

+

Add to project

↓

Data sheet as PDF

↔

Compare

≡+

Bookmark

📍

Find distributors

Overview

Data

Downloads

Related products

Customers also purchased

Item no. 2006-1204



Product details

Details ^

Electrical data

Rated voltage EN (Ex e II)	550 V
----------------------------	-------

Rated current (Ex e II)	38 A
-------------------------	------

Rated current (Ex e II) with jumper	33 A
-------------------------------------	------

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	800 V
-------------------------	-------

Rated impulse voltage (III / 3)	8 kV
---------------------------------	------

Rated current	41 A
---------------	------

Rated current (2)	57 A
-------------------	------

Legend (ratings)	(III / 3) $\triangleq$ Overvoltage category III / Pollution degree 3
------------------	--

Approvals per UL 1059

Rated voltage UL (Use Group B)	600 V
--------------------------------	-------

Rated current UL (Use Group B)	50 A
--------------------------------	------

Rated voltage UL (Use Group C)	600 V
--------------------------------	-------

Rated current UL (Use Group C)	50 A
--------------------------------	------

Approvals per CSA

Rated voltage CSA (Use Group B)	600 V
---------------------------------	-------

Rated current CSA (Use Group B)	50 A
---------------------------------	------

Rated voltage CSA (Use Group C)	600 V
---------------------------------	-------

Rated current CSA (Use Group C)	50 A
---------------------------------	------



Connection data

Item no. 2006-1204



Actuation type

Open Tool Slot

Connectable conductor materials	Copper
Nominal cross section	6 mm ²
Solid conductor	0.5 ... 10 mm ² / 20 ... 8 AWG

Geometrical Data

Width	7.5 mm / 0.295 inch
Height from upper-edge of DIN-35 rail	32.9 mm / 1.295 inch
Depth	57.5 mm / 2.264 inch

Mechanical data

Design	horizontal
Type of mounting	DIN-35 rail
Marking level	Center/side marking

Material Data

Color	blue
Insulating material	Polyamide 66 (PA 66)
Fire load	0.154 MJ
Weight	8.975 g

Commercial data

Country of Origin	DE
GTIN	4017332999656
Product Group	22 (TOPJOB S)



Downloads

Item no. 2006-1204

Documentation





Bid Text

2006-1204
Reihenklemmen, TOPJOB S
Aug 13, 2018

DOCX
15.1 kB

 German

- › Download
- › Bookmark

CAD Tles ^



Compatible products

Carrier rail ^

^ Show fewer ^ Show more

End plate ^

General accessories ^

Jumper ^

Marking accessories ^

Protective Warning Marker ^



Item no. 2006-1204



^



Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

> Show all products from the family.

> United States (EN)

> We are happy to help

☎ 1-800-DIN-RAIL (346-7245)



© 2018 WAGO Corporation

Contact

Careers

Item no. 2006-1204

Privacy



