



Availability

PU (SPU): 50 Piece

Add to projectData sheet as PDFCompareBookmarkFind distributors

Overview

Data

Approval

Downloads

Related products

Customers also purchased



Product details

Details ^

Electrical data

Rated voltage EN (Ex e II)	440 V
Rated current (Ex e II)	20 A
Rated current (Ex e II) with jumper	18 A

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	500 V
Rated impulse voltage (III / 3)	6 kV
Rated current	24 A
Rated current (2)	28 A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3

Approvals per UL 1059

Rated voltage UL (Use Group B)	300 V
Rated current UL (Use Group B)	20 A
Rated voltage UL (Use Group C)	300 V
Rated current UL (Use Group C)	20 A
Rated voltage UL (Use Group D)	600 V



Connection data

Item no. 2002-2209



Actuation typeOpen Tool Slot

Connectable conductor materials	Copper
Nominal cross section	2.5 mm²
Solid conductor	0.25 ... 4 mm² / 22 ... 12 AWG

Geometrical Data

Width	5.2 mm / 0.205 inch
Height from upper-edge of DIN-35 rail	51.7 mm / 2.035 inch
Depth	69.7 mm / 2.744 inch

Mechanical data

Design	horizontal
Type of mounting	DIN-35 rail
Potential marking	N
Marking level	Center/side marking

Material Data

Color	blue
Insulating material	Polyamide 66 (PA 66)
Fire load	0.209 MJ
Weight	10.716 g

Commercial data

Country of Origin	DE
GTIN	4044918691116
Product Group	22 (TOPJOB S)



Item no. 2002-2209



Ex-Approvals ^

Logo
Approval
CertiTcate name

Logo



Approval:
AEx
UL International Germany GmbH c/o Physikalisch Technische Bundesanstalt
CertiTcate name:
E185892 sec.7

English

PDF (535.0 kB)
» **Download**
» **Bookmark**

Logo



Approval:
ATEX
Physikalisch Technische Bundesanstalt (PTB)
CertiTcate name:
PTB 03 ATEX 1162 U (II 2 G/D Ex e II bzw. IM 2 Ex e I)

Logo



Approval:
IECEX
Physikalisch Technische Bundesanstalt
CertiTcate name:
IECEX PTB 03.0004U

English

PDF (1.9 MB)
» **Download**
» **Bookmark**

Country speciTc Approvals ^



approvals ^





Downloads

Documentation ^

Bid Text

2002-2209

Aug 13, 2018

DOCX

15.4 kB



German

- › Download
- › Bookmark

CAD Tles ^



Compatible products

Carrier rail ^



Show fewer



Show more

End plate ^

General accessories ^

Insulation stop ^



Item no. 2002-2209



ective Warning Marker ^

check ▾

ferrule ▾

plug ▾

tools ▾



Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

> Show all products from the family.

> United States (EN)

> We are happy to help



IN-RAIL (346-7245)

Item no. 2002-2209



© 2018 WAGO Corporation

[Contact](#)

[Careers](#)

[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)