



TOPJOB® S > TOPJOB®S feedthrough terminal block; rail mount;
3-conductor; 10 mm wide; gray

Price and availability after [Login](#)


Availability 





PU (SPU): 25 Piece

-

25

+

 Add to project

-  Data sheet as PDF
-  Compare
-  Bookmark
-  Find distributors

Overview

Data

Downloads

Related products

Customers also purchased





Product details

Details ^

Electrical data

| | |
|----------------------------|-------|
| Rated voltage EN (Ex e II) | 550 V |
|----------------------------|-------|

| | |
|-------------------------|------|
| Rated current (Ex e II) | 50 A |
|-------------------------|------|

Ratings per IEC/EN 60664-1

| | |
|-------------------------|-------|
| Rated voltage (III / 3) | 800 V |
|-------------------------|-------|

| | |
|---------------------------------|------|
| Rated impulse voltage (III / 3) | 8 kV |
|---------------------------------|------|

| | |
|---------------|------|
| Rated current | 57 A |
|---------------|------|

| | |
|-------------------|------|
| Rated current (2) | 76 A |
|-------------------|------|

| | |
|------------------|-----------------------------------------------------------|
| Legend (ratings) | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |
|------------------|-----------------------------------------------------------|

Approvals per UL 1059

| | |
|--------------------------------|-------|
| Rated voltage UL (Use Group B) | 600 V |
|--------------------------------|-------|

| | |
|--------------------------------|------|
| Rated current UL (Use Group B) | 65 A |
|--------------------------------|------|

| | |
|--------------------------------|-------|
| Rated voltage UL (Use Group C) | 600 V |
|--------------------------------|-------|

| | |
|--------------------------------|------|
| Rated current UL (Use Group C) | 65 A |
|--------------------------------|------|

Approvals per CSA

| | |
|---------------------------------|-------|
| Rated voltage CSA (Use Group B) | 600 V |
|---------------------------------|-------|

| | |
|---------------------------------|------|
| Rated current CSA (Use Group B) | 65 A |
|---------------------------------|------|

| | |
|---------------------------------|-------|
| Rated voltage CSA (Use Group C) | 600 V |
|---------------------------------|-------|

| | |
|---------------------------------|------|
| Rated current CSA (Use Group C) | 65 A |
|---------------------------------|------|

Connection data

Connection technology

Push-in CAGE CLAMP®

Item no. 2010-1301



Connectable conductor materials

Copper

| | |
|-----------------------|--------|
| Nominal cross section | 10 mm² |
|-----------------------|--------|

| | |
|-----------------|-------------------------------|
| Solid conductor | 0.5 ... 16 mm² / 20 ... 6 AWG |
|-----------------|-------------------------------|

Geometrical Data

| | |
|-------|--------------------|
| Width | 10 mm / 0.394 inch |
|-------|--------------------|

| | |
|---------------------------------------|----------------------|
| Height from upper-edge of DIN-35 rail | 36.9 mm / 1.453 inch |
|---------------------------------------|----------------------|

| | |
|-------|--------------------|
| Depth | 89 mm / 3.504 inch |
|-------|--------------------|

Mechanical data

| | |
|--------|------------|
| Design | horizontal |
|--------|------------|

| | |
|------------------|-------------|
| Type of mounting | DIN-35 rail |
|------------------|-------------|

| | |
|---------------|---------------------|
| Marking level | Center/side marking |
|---------------|---------------------|

Material Data

| | |
|-------|------|
| Color | gray |
|-------|------|

| | |
|---------------------|----------------------|
| Insulating material | Polyamide 66 (PA 66) |
|---------------------|----------------------|

| | |
|-----------|----------|
| Fire load | 0.381 MJ |
|-----------|----------|

| | |
|--------|--------|
| Weight | 24.7 g |
|--------|--------|

Commercial data

| | |
|-------------------|----|
| Country of Origin | DE |
|-------------------|----|

| | |
|------|---------------|
| GTIN | 4017332011341 |
|------|---------------|

| | |
|---------------|---------------|
| Product Group | 22 (TOPJOB S) |
|---------------|---------------|



Downloads

Item no. 2010-1301



Bid Text

2010-1301
Reihenklemmen, TOPJOB S
Aug 13, 2018

DOCX

15.2 kB



German

- › Download
- › Bookmark

CAD Tles ^



Compatible products

Carrier rail ^



Show fewer



Show more

End plate ^

General accessories ^

Jumper ^

Marking accessories ^

Protective Warning Marker ^

check ^



Item no. 2010-1301





Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

> Show all products from the family.

> United States (EN)

> We are happy to help

📞 1-800-DIN-RAIL (346-7245)



© 2018 WAGO Corporation

Contact

Careers

Imprint

Item no. 2010-1301



