

Customers also purchased



Product details

Details ^

Connection data

Connection technology	Push-in CAGE CLAMP®
Actuation type	Open Tool Slot
Connectable conductor materials	Copper
Nominal cross section	6 mm²
Solid conductor	0.5 10 mm² / 20 8 AWG

Geometrical Data

Width	7.5 mm / 0.295 inch
Height from upper-edge of DIN-35 rail	32.9 mm / 1.295 inch
Depth	73.5 mm / 2.894 inch

Mechanical data

Design	horizontal
Type of mounting	DIN-35 rail
Marking level	Center/side marking

Material Data



Color	green-yellow
Insulating material	Polyamide 66 (PA 66)
Fire load	0.187 MJ
Weight	20.285 g
Commercial data	

Country of Origin	DE
GTIN	4017332999717
Product Group	22 (TOPJOB S)



Approvals / CertiTcates

Country speciTc Approvals ^

Logo Approval CertiTcate name

Logo



Approval: CCA

DEKRA CertiTcation B.V.

CertiTcate name: NTR NL 7311

English

PDF (5.7 MB)

Download

Bookmark

Logo



Item no. 2006-1307





Approval: CSA

DEKRA CertiTcation B.V.

CertiTcate name:

1543858



PDF (40.1 kB)

- Download
- Bookmark

Ship Approvals `

UL-Approvals `



Downloads

Documentation ^



Bid Text

2006-1307 Reihenklemmen, TOPJOB S Aug 13, 2018

DOCX 15.0 kB

German

ownload ookmark



Compatible products

Carrier rail ^
^ Show fewer
End plate *
General accessories *
Jumper *
Marking accessories *
Warking accessories
Protective Warning Marker *
check ~
ferrule
tools



Product family



TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

> Show all products from the family.

> United States (EN)

> We are happy to help

1-800-DIN-RAIL (346-7245)











© 2018 WAGO Corporation
Contact
Careers
Imprint
Privacy
Terms and Conditions
Legal