



PU (SPU): 1 Piece

—

1

+

 Add to project

 Data sheet as PDF

 Compare

 Bookmark

 Find distributors

## Overview

## Data

## Approval

## Downloads

## Related products

## Customers also purchased

## Description

### Note on Continuous Service Temperature:

-35°C ... +85°C

PVC cable for temperatures = 70 °C (including halogen-free)

Insulating parts for temperatures = 105 °C

Only in mated condition with strain relief housing (These compact connectors are not designed for use in open, easily accessible areas)



## Product details

### Details ^

#### — Electrical data

##### — Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	250 V
Rated impulse voltage (III / 3)	4 kV
Rated current	20 A
Legend (ratings)	(III / 3) $\triangleq$ Overvoltage category III / Pollution degree 3

#### — Connection data

length

9 mm / 0.35 Inch

of poles

3

**Item no. 771-9993/207-502**



Ground function

with preceding GND contact

## — Geometrical Data

Pin spacing 10 mm (0.394 inch)

Total length 5 m

## — Mechanical data

Coding A

Mating force of a plug-in connection approx. 20 ... 70 N (depending on pole number)

Retention force of a plug-in connection when locked: > 80N

Unmating force of a plug-in connection when unlocked: approx. 20 ... 70 N (depending on pole number)

Connection type cable/adapter 1 1 Plug

## — Plug connection

Mismating protection Yes

Locking of plug-in connection locking lever

Locking lever no

## — Material Data

Color white

Insulating material Polyamide 66 (PA 66)

Flammability class per UL94 V0

Reaction to Tre class per EN 50575 E<sub>ca</sub>

Contact material Copper or copper alloy, surface-treated

## — Environmental Requirements



Surrounding air (operating) temperature	-35 ... 85 °C
Processing temperature	-5°C ... +40°C
Continuous operating temperature from	-35 °C
Continuous operating temperature up to	85 °C

## Commercial data

Country of Origin	DE
GTIN	4044918273015
Product Group	20 (WINSTA)



## Approvals / Certificates

### Country specific Approvals ^

Logo  
Approval  
Certificate name

Logo

**CCA**

Approval:  
**CCA**  
DEKRA Certification B.V.  
Certificate name:  
NTR NL-7355

 English

PDF (2.6 MB)  
[Download](#)  
[Bookmark](#)

Logo

**KEMA  
JR**

Approval:  
**/KEUR**

**Item no. 771-9993/207-502**



English



## Downloads

### Documentation ^

#### — Bid Text

771-9993/207-502  
WINSTA MIDI 3-polig  
Feb 2, 2016



DOC

27.1 kB

Germany German

› Download  
› Bookmark



## Compatible products

### Locking lever ^

^ Show fewer    ▼ Show more

### Marking accessories ^

### protection ^



Item no. 771-9993/207-502



Product family

# WINSTA MIDI

› Show all products from the family.

› United States (EN)

› We are happy to help

📞 1-800-DIN-RAIL (346-7245)



Item no. 771-9993/207-502



© 2018 WAGO Corporation

[Contact](#)

[Careers](#)

[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)

**Item no. 771-9993/207-502**