



Availability

PU (SPU): 25 Piece



 Add to project

 Data sheet as PDF

 Compare

 Bookmark

 Find distributors

Overview

Data

Downloads

Related products

Customers also purchased

Family

Description

Note on Continuous Service Temperature:

-35°C to +85°C

Insulating parts for temperatures = 105°C



Product details

Details ^

— Connection data

No. of poles	3
Connectable sheathed cable diameter	8 ... 11.5 mm

— Mechanical data

Degree of protection	IP20
----------------------	------

— Material Data

Color	black
Insulating material	Polyamide 66 (PA 66)
Flammability class per UL94	V0
Fire load	0.332 MJ
Weight	12 g



Environmental Requirements

Item no. 770-503/032-000



Processing temperature

-5°C ... +40°C

Continuous operating temperature from

-35 °C

Continuous operating temperature up to

85 °C

Commercial data

Country of Origin

DE

GTIN

4044918102421

Product Group

20 (WINSTA)



Downloads

Documentation ^

Bid Text

770-503/032-000

WINSTA MIDI 3-polig

Feb 1, 2016



DOC

24.1 kB

 German

- › [Download](#)
- › [Bookmark](#)



Compatible products



accessories ^

Item no. 770-503/032-000





WINSTA MIDI

› Show all products from the family.

› United States (EN)

› We are happy to help

📞 **1-800-DIN-RAIL (346-7245)**



© 2018 WAGO Corporation

Contact

Careers



Item no. 770-503/032-000



Privacy

