



Availability ✓

PU (SPU): 1 Piece



Add to project

Data sheet as PDF

Compare

Bookmark

Find distributors

Overview

Data

Approval

Downloads

Related products

Customers also purchased

Description

Note on Continuous Service Temperature:

-35°C ... +85°C

PVC cable for temperatures = 70 °C (including halogen-free)

Insulating parts for temperatures = 105 °C

Only in mated condition with strain relief housing (These compact connectors are not designed for use in open, easily accessible areas)



Product details

Details ^

— Electrical data

— Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	250 V
Rated impulse voltage (III / 3)	4 kV
Rated current	20 A
Legend (ratings)	(III / 3) \triangleq Overvoltage category III / Pollution degree 3

— Connection data

length

9 mm / 0.35 Inch

of poles

3

Item no. 771-9993/207-302



Ground function

with preceding GND contact

— Geometrical Data

Pin spacing 10 mm (0.394 inch)

Total length 3 m

— Mechanical data

Coding A

Mating force of a plug-in connection approx. 20 ... 70 N (depending on pole number)

Retention force of a plug-in connection when locked: > 80N

Unmating force of a plug-in connection when unlocked: approx. 20 ... 70 N (depending on pole number)

Connection type cable/adapter 1 1 Plug

— Plug connection

Mismating protection Yes

Locking of plug-in connection locking lever

Locking lever no

— Material Data

Color white

Insulating material Polyamide 66 (PA 66)

Flammability class per UL94 V0

Reaction to Tre class per EN 50575 E_{ca}

Contact material Copper or copper alloy, surface-treated

— Environmental Requirements



Surrounding air (operating) temperature	-35 ... 85 °C
Processing temperature	-5°C ... +40°C
Continuous operating temperature from	-35 °C
Continuous operating temperature up to	85 °C

Commercial data

Country of Origin	DE
GTIN	4044918272995
Product Group	20 (WINSTA)



Approvals / Certificates

Country specific Approvals ^

Logo
Approval
Certificate name

Logo

CCA

Approval:
CCA
DEKRA Certification B.V.
Certificate name:
NTR NL-7355

 English

PDF (2.6 MB)
[Download](#)
[Bookmark](#)

Logo

**KEMA
UR**

Approval:
/KEUR

Item no. 771-9993/207-302



English



Downloads

Documentation ^

— Bid Text

771-9993/207-302
WINSTA MIDI 3-polig
Feb 2, 2016



DOC

27.1 kB

Germany German

› Download
› Bookmark



Compatible products

Locking lever ^

^ Show fewer ▼ Show more

Marking accessories ^

protection ^



Item no. 771-9993/207-302



Product family

WINSTA MIDI

› Show all products from the family.

› United States (EN)

› We are happy to help

📞 1-800-DIN-RAIL (346-7245)



Item no. 771-9993/207-302



© 2018 WAGO Corporation

[Contact](#)

[Careers](#)

[Imprint](#)

[Privacy](#)

[Terms and Conditions](#)

[Legal](#)

Item no. 771-9993/207-302