

Datablad | Artikkelnummer: 709-583

Bryterutstyr-uttaksskap; for DIN-skinne- og skruemontering; for plugg, type F, CEE 7/4 (Schuko); vanlig i DE, NL, AT; med LED-statusindikator; med Push-in Cage Clamp med dobbel kobling



www.wago.com/709-583



RoHS
Compliant

BOMcheck.net

Farge: ■



Data

Electrical data

Voltage type (1)

AC

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	250 V
Rated impulse voltage (III / 3)	2 kV
Rated current	16 A

Connection data

Connection type (1)	L, PE, N
Connection technology	Push-in CAGE CLAMP®
Actuation type	Push-in
Actuation direction (1)	Operation parallel to conductor entry
Connectable conductor materials	Copper
Nominal cross section	2.5 mm ²
Solid conductor	0.2 ... 2.5 mm ² / 24 ... 14 AWG
Stranded conductor	0.2 ... 2.5 mm ² / 24 ... 14 AWG
Fine-stranded conductor	0.2 ... 2.5 mm ² / 24 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 Inch
No. of poles	3
Number of connection types	3
Number of test slots	2

Geometrical Data

Width	45 mm / 1.772 inch
Height	65 mm / 2.559 inch
Høyde fra overflaten	65 mm / 2.559 inch
Høyde fra øverste kant av DIN-skinne	59.8 mm / 2.354 inch
Depth	84.7 mm / 3.335 inch

Mechanical data

Type of mounting	DIN-35 rail
Degree of protection	IP20
Potential marking	L N

Material Data

Color	rød
Material group	I
Insulating material	Polyamide 66 (PA 66)
Flammability class per UL94	V0
Clamping spring material	Chrome nickel spring steel (CrNi)



Contact material	Copper alloy
Contact plating	Sn
Weight	81.6 g

Commercial data

Packaging type	BOX
Country of origin	BG
GTIN	4055143718301

Godkjenninger/sertifikater**Landspesifikke godkjenninger**

Logo	Godkjenning	Sertifikatnavn
	VDE VDE Prüf- und Zertifizierungsinstitut	40047680 (IEC 60884-1)

Nedlastinger**smartDATA****CAD data**

3D Download 709-583	URL	Last ned
---------------------	-----	----------

Forbehold om endringer.

WAGO Norge

Har du spørsmål om våre produkter?

Vi tar alltid gjerne imot di samtale på 22 30 94 50.