

---

|                      |                                                                                                                                                  |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Item no.:            | 770-213                                                                                                                                          |
| Product description: | PLUG; WITHOUT RELIEF HOUSING; 3 POLE; PIN SPACING<br>10 MM / 0.394 IN; 100% PROTECTED AGAINST MISMATING;<br>CAGE CLAMP <sup>®</sup> S CONNECTION |

---



Packing unit 100 pieces

|                                       |                                            |
|---------------------------------------|--------------------------------------------|
| Product group                         | 20 (WINSTA)                                |
| pole count                            | 3                                          |
| Cross section from [mm <sup>2</sup> ] | 0,5 mm <sup>2</sup>                        |
| Cross section to [mm <sup>2</sup> ]   | 4 mm <sup>2</sup>                          |
| Cross section from [AWG]              | 20 AWG                                     |
| Cross section to [AWG]                | 12 AWG                                     |
| Connection method                     | CONTACT CAGE CLAMP <sup>®</sup> CONNECTION |
| Number of strands                     | 2                                          |
| Measured voltage EN                   | 250 V                                      |
| Measured shock voltage                | 4 kV                                       |
| Pollution degree                      | 3                                          |
| Current intensity EN                  | 25 A                                       |
| Weight                                | 10,002 g                                   |
| Color                                 | black                                      |
| No. of connection Points              | 6                                          |
| No. of potentials                     | 3                                          |
| Height                                | 12,9 mm                                    |
| Height                                | 0,508 in                                   |
| Width                                 | 30 mm                                      |
| Width                                 | 1,181 in                                   |
| Depth                                 | 37,5 mm                                    |
| Depth                                 | 1,476 in                                   |
| Strip length from                     | 9 mm                                       |
| Strip length to                       | 9 mm                                       |
| Strip length                          | 0,35 in                                    |



| Item number | Admission office | Approval no.      | Voltage [V] | Current [A] | Cross section [ mm² ] |
|-------------|------------------|-------------------|-------------|-------------|-----------------------|
| 770-213     | CBCertificateVDE | DE1-29543         | 250/400     | 25          | 0,5-4                 |
| 770-213     | CCA              | NL5566            | 250         | 25          | 0,5-4,0               |
| 770-213     | cURus            | E45171            | 600         | 20          | 12                    |
| 770-213     | DNV              | E6188             | 250         | 25          | 4                     |
| 770-213     | GL               | 42875-02HH        | 250         | 25          | 4                     |
| 770-213     | KEMA             | 2060958.02        | 250         | 25          | 0,5-4,0               |
| 770-213     | LR               | 02/20050(E3)      | 250         | 25          | 2,5                   |
| 770-213     | PRS              | TE/1719/880590/08 | 250         | 25          | 0,5-4,0               |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected