
Item no.: 770-233

Product description: PLUG; WITHOUT RELIEF HOUSING; 3 POLE; PIN SPACING 10 MM / 0.394 IN; 100% PROTECTED AGAINST MISMATING; CAGE CLAMP[®]S CONNECTION



Packing unit 100 pieces

Product group	20 (WINSTA)
pole count	3
Cross section from [mm²]	0,5 mm²
Cross section to [mm²]	4 mm²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Connection method	CONTACT CAGE CLAMP [®] CONNECTION
Number of strands	2
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	25 A
Weight	10,105 g
Color	white
No. of connection Points	6
No. of potentials	3
Height	12,9 mm
Height	0,508 in
Width	30 mm
Width	1,181 in
Depth	37,5 mm
Depth	1,476 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0,35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
770-233	CBCertificateVDE	DE1-29543	250/400	25	0,5-4
770-233	CCA	NL5567	250	25	0,5-4,0
770-233	cURus	E45171	600	20	12
770-233	DNV	E6188	250	25	4
770-233	GL	42875-02HH	250	25	4
770-233	KEMA	2060958.02	250	25	0,5-4,0
770-233	LR	02/20050(E3)	250	25	2,5
770-233	PRS	TE/1719/880590/08	250	25	0,5-4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected