


Item no.: 770-2334/007-000

Product description: PLUG; SNAP IN TYPE; 4 POLE; CODING Q (CLEAN EARTH APPLICATIONS); 100% PROTECTED AGAINST MISMATING; WITH DIRECT CONTACT OF THE EARTH CONDUCTOR



Packing unit 50 pieces

Product group	20 (WINSTA)
pole count	4
Cross section from [mm ²]	0,5 mm ²
Cross section to [mm ²]	4 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Number of strands	2
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	32 A
Weight	17,715 g
Color	green
No. of connection Points	4
No. of potentials	4
Height	18,5 mm
Height	0,728 in
Width	45,5 mm
Width	1,791 in
Depth	37,5 mm
Depth	1,476 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0,35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
770-2334/007-000	CCA	NL5637	400	25	0,5-4,0
770-2334/007-000	KEMA	2077836.01	400	32	0,5-4,0
770-2334/007-000	PRS	TE/1719/880590/08	400	25	0,5-4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected