


Item no.: 770-235
Product description: PLUG; WITHOUT RELIEF HOUSING; 5 POLE; PIN SPACING 10 MM / 0.394 IN; 100% PROTECTED AGAINST MISMATING; CAGE CLAMP[®]S CONNECTION



Packing unit 50 pieces

Product group	20 (WINSTA)
pole count	5
Cross section from [mm ²]	0,5 mm ²
Cross section to [mm ²]	4 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Connection method	CONTACT CAGE CLAMP [®] CONNECTION
Number of strands	2
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	25 A
Weight	16,445 g
Color	white
No. of connection Points	10
No. of potentials	5
Height	12,9 mm
Height	0,508 in
Width	50 mm
Width	1,969 in
Depth	37,5 mm
Depth	1,476 in



Strip length from	9 mm
Strip length to	9 mm
Strip length	0,35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
770-235	CBCertificateVDE	DE1-29543	250/400	25	0,5-4
770-235	CCA	NL5567	400	25	0,5-4,0
770-235	cURus	E45171	600	20	12
770-235	DNV	E6188	400	25	4
770-235	GL	42875-02HH	400	25	4
770-235	KEMA	2060958.02	400	25	0,5-4,0
770-235	LR	02/20050(E3)	250	25	2,5
770-235	PRS	TE/1719/880590/08	400	25	0,5-4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected