
Item no.: 770-688

Product description: DISTRIBUTION CONNECTOR FOR SINGLE-POLE SWITCH OR TWO-WAY CIRCUITS; PLUGABLE; 3 POLE; 1 x PLUG CODING A, LOCKING DEVICE WHITE; 2 x SOCKET CODING A, LOCKING DEVICE WHITE; 1 x SOCKET CODING A (LIGHT), LOCKING DEVICE BLACK



Packing unit 10 pieces

| | |
|------------------------|-------------|
| Product group | 20 (WINSTA) |
| pole count | 3 |
| Measured voltage EN | 250 V |
| Measured shock voltage | 4 kV |
| Pollution degree | 3 |
| Current intensity EN | 25 A |
| Weight | 43,191 g |
| Color | white |
| Height | 52,5 mm |
| Height | 2,07 in |
| Width | 38 mm |
| Width | 1,496 in |
| Depth | 46 mm |
| Depth | 1,811 in |



| Item number | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|-------------|------------------|-------------------|-------------|-------------|-----------------------------------|
| 770-688 | CCA | NL5568 | 250 | 25 | 0,5-4,0 |
| 770-688 | KEMA | 2060958.03 | 250 | 25 | 0,5-4,0 |
| 770-688 | KEMA | 2060958.04 | 250 | 25 | 0,5-4,0 |
| 770-688 | PRS | TE/1719/880590/08 | 250 | 25 | 0,5-4,0 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected