



Item no.: 770-725  
 Product description: SOCKET; SNAP IN TYPE; 5 POLE; 100% PROTECTED AGAINST MISMATING; CAGE CLAMP®S CONNECTION



Packing unit 100 pieces

Product group	20 (WINSTA)
pole count	5
Cross section from [mm <sup>2</sup> ]	0,5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Connection method	CONTACT CAGE CLAMP®CONNECTION
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	25 A
Weight	19,25 g
Color	white
No. of connection Points	10
No. of potentials	5
Height	18,5 mm
Height	0,728 in
Width	55,5 mm
Width	2,185 in
Depth	36 mm
Depth	1,417 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0,35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
770-725	CCA	NL5569	400	25	0,5-4,0
770-725	cURus	E45171	600	20	12
770-725	DNV	E6188	250	25	4
770-725	GL	42875-02HH	250	25	4
770-725	KEMA	2060958.04	400	25	0,5-4,0
770-725	LR	02/20050(E3)	250	20	2,5
770-725	PRS	TE/1719/880590/08	400	25	0,5-4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected