

---

Item no.: 770-753  
Product description: PLUG; SNAP IN TYPE; 3 POLE; 100% PROTECTED  
AGAINST MISMATING; CAGE CLAMP®S CONNECTION

---



Packing unit 100 pieces

|                          |                               |
|--------------------------|-------------------------------|
| Product group            | 20 (WINSTA)                   |
| pole count               | 3                             |
| Cross section from [mm²] | 0,5 mm²                       |
| Cross section to [mm²]   | 4 mm²                         |
| Cross section from [AWG] | 20 AWG                        |
| Cross section to [AWG]   | 12 AWG                        |
| Connection method        | CONTACT CAGE CLAMP®CONNECTION |
| Number of strands        | 2                             |
| Measured voltage EN      | 250 V                         |
| Measured shock voltage   | 4 kV                          |
| Pollution degree         | 3                             |
| Current intensity EN     | 25 A                          |
| Weight                   | 11,488 g                      |
| Color                    | grey                          |
| No. of connection Points | 6                             |
| No. of potentials        | 3                             |
| Height                   | 17,5 mm                       |
| Height                   | 0,689 in                      |
| Width                    | 35,5 mm                       |
| Width                    | 1,398 in                      |
| Depth                    | 36 mm                         |
| Depth                    | 1,417 in                      |
| Strip length from        | 9 mm                          |
| Strip length to          | 9 mm                          |
| Strip length             | 0,35 in                       |



| Item number | Admission office | Approval no.      | Voltage [V] | Current [A] | Cross section [ mm² ] |
|-------------|------------------|-------------------|-------------|-------------|-----------------------|
| 770-753     | CCA              | NL5568            | 250         | 25          | 0,5-4,0               |
| 770-753     | cURus            | E45171            | 600         | 20          | 12                    |
| 770-753     | KEMA             | 2060958.03        | 250         | 25          | 0,5-4,0               |
| 770-753     | PRS              | TE/1719/880590/08 | 250         | 25          | 0,5-4,0               |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected