

Item no.: 770-833
Product description: PLUG; FOR PRINTED CIRCUIT BOARD; 3 POLE; STRAIGHT
MODULE FORMATION; PIN SPACING 10 MM / 0.394 IN;
100% PROTECTED AGAINST MISMATING



Packing unit 100 pieces

| | |
|--------------------------|-------------|
| Product group | 20 (WINSTA) |
| pole count | 3 |
| Measured voltage EN | 250 V |
| Measured shock voltage | 4 kV |
| Pollution degree | 3 |
| Current intensity EN | 25 A |
| Weight | 15,72 g |
| Color | white |
| No. of connection Points | 3 |
| No. of potentials | 3 |
| Height | 26 mm |
| Height | 1,024 in |
| Width | 27 mm |
| Width | 1,063 in |
| Depth | 11,7 mm |
| Depth | 0,461 in |



| Item number | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|-------------|------------------|-------------------|-------------|-------------|-----------------------------------|
| 770-833 | CCA | NL5568 | 250 | 25 | 0,5-4,0 |
| 770-833 | cURus | E45171 | 600 | 20 | 12 |
| 770-833 | KEMA | 2060958.03 | 250 | 25 | 0,5-4,0 |
| 770-833 | PRS | TE/1719/880590/08 | 250 | 25 | 0,5-4,0 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected