



KSM SIDE OPERATED POLYCARBONATE SWITCHES 16A & 25A

- Easy to install
- IP67
- Fully rated Load Break Switch
- Good resistance against UV and many chemicals
- Membrane gasket cable entries as standard with strain relief 2 x 20 mm on the top, 2 x 20 mm on the bottom and 2 x 15 mm on the base
- Possible to install M20 cable glands
- Wall mounting with membrane gaskets
- Wall mounting dimensions: 62,0 x 90,0 mm
- Large cable terminals 1,5 - 16 mm²
- Padlockable handle to OFF-position
- Handle sealable to ON-position
- Enclosure can be sealed to any position
- Available 2, 3, 4P and 3P with auxiliary contact (S)
- Large 1,5 - 16 mm² neutral and earth terminals on 3P switch, earth on 2P and 4P switches

CERTIFICATES



Type	AC-21	415 V	AC-22	415 V	AC-23	415 V	Poles	EAN code	Weight
	Ie/A		Ie/A		Ie/A				
Grey / Black									
16 A									
KSM 216U	16 A		16 A		16 A		2P	6419410328217	0,21
KSM 316U	16 A		16 A		16 A		3P	6419410328200	0,28
KSM 416U	16 A		16 A		16 A		4P	6419410328224	0,28
KSM 316US	16 A		16 A		16 A		3P + auxiliary contact	6419410328231	0,31
25 A									
KSM 225U	25 A		25 A		25 A		2P	6419410328330	0,21
KSM 325U	25 A		25 A		25 A		3P	6419410328309	0,28
KSM 425U	25 A		25 A		25 A		4P	6419410328316	0,28
KSM 325US	25 A		25 A		25 A		3P + auxiliary contact	6419410328323	0,31
Yellow / Red									
16 A									
KSM 216 Y/R	16 A		16 A		16 A		2P	6419410328170	0,21
KSM 316 Y/R	16 A		16 A		16 A		3P	6419410328163	0,28
KSM 416 Y/R	16 A		16 A		16 A		4P	6419410328187	0,28
KSM 316S Y/R	16 A		16 A		16 A		3P + auxiliary contact	6419410328194	0,31
25 A									

Type	AC-21 415 V	AC-22 415 V	AC-23 415 V	Poles	EAN code	Weight
	Ie/A	Ie/A	Ie/A			
KSM 225 Y/R	25 A	25 A	25 A	2P	6419410328460	0,21
KSM 325 Y/R	25 A	25 A	25 A	3P	6419410328477	0,28
KSM 425 Y/R	25 A	25 A	25 A	4P	6419410328484	0,28
KSM 325S Y/R	25 A	25 A	25 A	3P + auxiliary contact	6419410328491	0,31

Data subject to change without notice