

CURRENT/VOLTAGE MEASUR. MODULE; SET CURRENT 20...200A; VOLTAGE DETECTION UP TO 690V; OVERALL WIDTH 120MM; STRAIGHT-THROUGH CT



Figure similar

product brandname	SIRIUS
Product designation	Current/voltage measuring module
General technical data	
Product function	
• Current measurement	Yes
• voltage measurement	Yes
• active power measurement	Yes
• Power measurement	Yes
• frequency measurement	No
Product component	
• input for thermistor connection	No
Insulation voltage	
• with degree of pollution 3 rated value	690 V
Surge voltage resistance rated value	8 000 V
Protection class IP	IP20
Shock resistance	
• acc. to IEC 60068-2-27	15g / 11 ms

Vibration resistance	1-6 Hz / 15 mm; 6-500 Hz / 2 g
Equipment marking	F
• acc. to DIN EN 81346-2	
Electromagnetic compatibility	
EMC emitted interference	class A
• acc. to IEC 60947-1	
Conducted interference	2 kV
• due to burst acc. to IEC 61000-4-4	
• due to conductor-earth surge acc. to IEC 61000-4-5	2 kV
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Inputs/ Outputs	
Number of outputs as contact-affected switching element	0
Protective and monitoring functions	
Product function	Yes
• power factor monitoring	
• voltage detection	Yes
Motor protection functions	
Product function	Yes
• Current detection	
• Overload protection	Yes
Installation/ mounting/ dimensions	
Mounting position	any
Mounting type	screw and snap-on mounting
Height	95 mm
Width	120 mm
Depth	145 mm
Required spacing	30 mm
• top	
• bottom	30 mm
• left	0 mm
• right	0 mm
Connections/Terminals	
Type of electrical connection	straight-through transformers
• for main current circuit	
• for auxiliary and control current circuit	screw-type terminals
Type of electrical connection at the measurement inputs for voltage	screw-type terminals

Type of connectable conductor cross-sections	
• at the measurement inputs for voltage finely stranded with core end processing • at the measurement inputs for voltage solid • at the measurement inputs for voltage at AWG conductors solid	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²) 1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²) 1x (20 ... 14), 2x (20 ... 14)
Tightening torque at measuring inputs for voltage	0.8 ... 1.2 N·m
Tightening torque [lbf·in] at measuring inputs for voltage	7 ... 10.3 lbf·in

Ambient conditions

Ambient temperature	
• during operation • during storage • during transport	-25 ... +60 °C -40 ... +80 °C -40 ... +80 °C
Relative humidity	
• during operation	5 ... 95 %

Short-circuit protection

Product function Short circuit protection	No
--	----

Main circuit

Number of poles for main current circuit	3
Adjustable pick-up value current of the current-dependent overload release	20 ... 200 A
Operating voltage	
• at AC — at 50 Hz rated value — at 60 Hz rated value	110 ... 690 V 110 ... 690 V
Operating frequency rated value	50 ... 60 Hz

Control circuit/ Control

Type of voltage	AC
Type of voltage of the control supply voltage	AC

Certificates/approvals

General Product Approval	EMC	For use in hazardous locations
--------------------------	-----	--------------------------------



For use in hazardous locations	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------------	---------------------------	-------------------	-------------------

[Explosion Protection Certificate](#)



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



Shipping Approval	other
-------------------	-------



[Confirmation](#)

[PROFINET-Certification](#)

[PROFIsafe-Certification](#)



Profibus

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7113-1AA00-0>

Cax online generator




<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7113-1AA00-0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7113-1AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7113-1AA00-0&lang=en





last modified:

07/22/2017