

Similar to image

CIRCUIT-BREAKER VL 160N STANDARD BREAKING
CAPACITY ICU=55KA / 415 V AC 4 POLE,
NON-AUTOMATIC OVERCURRENT RELEASE MAGNETIC
IN=160A,
RATED CURRENT II=2500A, SHORT-CIRCUIT

General technical data:

Number of poles		4
Design of the overcurrent release		M
Acceptability for application		non-automatic circuit-breakers
Electrical operating cycles as operating time / typical		10,000
Mechanical operating cycles as operating time / typical		20,000
Active power loss / maximum	W	40
Product component		
• auxiliary switch		No
• Voltage trigger		No
• undervoltage release mechanism		No
• undervoltage release with leading contact		No
Product function		
• of the thermal overload release		Without
• ground-fault protection		No
• for zero conductors / short-circuit and overload protection		No
• overload protection		No
Operating cycles / maximum	1/s	120
Protection class IP		IP20
Protective function of the overcurrent release		I
Impulse voltage resistance / rated value	kV	8
Ambient temperature		
• during operating		
• minimum	°C	-25 ...
• maximum	°C	70
• during storage		
• minimum	°C	-40
• maximum	°C	50

Main circuit:

Insulation voltage / for AC / rated value	V	800
---	---	-----

Operating frequency • 1 / rated value • 2 / rated value	Hz	50
	Hz	60
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		Q
		Q
Operating voltage • for main current circuit • at 50 Hz / for AC • maximum • at 60 Hz / for AC • maximum • for DC • maximum	V	690
	V	690
	V	500
Operating current • at 40 °C / rated value • at 50 °C / rated value • at 60 °C / rated value • at 70 °C / rated value	A	160
	A	160
	A	148.8
	A	137.6
Continuous current / rated value	A	160
Derating temperature / for the rated value of the continuous current	°C	50

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts

0

Number of NO contacts / for auxiliary contacts

0

Short-circuit:

Adjustable response current

- of the current-dependent overload release

- initial value

...

- of the non-delayed short-circuit release

- initial value

A

2,500 ...

- final value

A

2,500

Breaking capacity limit short-circuit current (I_{cu}) / at 415 V / rated value

kA

55

Installation/mounting/dimensions:

Type of mounting

fixed mounting

Height

mm

174.5

Width

mm

139.5

Depth	mm	106.5
--------------	----	-------

Connections:

Arrangement of electrical connectors / for main current circuit		front side
Design of the electrical connection / for main current circuit		box terminals
Type of the connectable conductor cross-section		
• for main contacts • with flexible busbar • solid • finely stranded / with conductor end processing • stranded • for auxiliary contacts • solid • finely stranded / with conductor end processing		12 x 10 mm 2,5 ... 95 mm ² 2,5 ... 50 mm ² 2,5 ... 95 mm ² 0,75 ... 1.5 mm ² 0.75 ... 1.0 mm ²

Certificates/approvals:

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL2716-1EE43-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2716-1EE43-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 8, 2013