

Similar to image

CIRCUIT-BREAKER VL 400H HIGH BREAKING CAPACITY
ICU=70KA / 415 V AC 4 POLE,
NON-AUTOMATIC OVERCURRENT RELEASE MAGNETIC
IN=400A,
RATED CURRENT II=4000A, SHORT CIRCUIT

General technical data:

Number of poles		4
Design of the overcurrent release		M
Acceptability for application		non-automatic circuit-breakers
Electrical operating cycles as operating time / typical		10,000
Mechanical operating cycles as operating time / typical		20,000
Active power loss / maximum	W	90
Product component		
• auxiliary switch		No
• Voltage trigger		No
• undervoltage release mechanism		No
• undervoltage release with leading contact		No
Product function		
• of the thermal overload release		Without
• ground-fault protection		No
• for zero conductors / short-circuit and overload protection		No
• overload protection		No
Operating cycles / maximum	1/s	120
Protection class IP		IP20
Protective function of the overcurrent release		I
Impulse voltage resistance / rated value	kV	8
Ambient temperature		
• during operating		
• minimum	°C	-25 ...
• maximum	°C	70
• during storage		
• minimum	°C	-40
• maximum	°C	50

Main circuit:

Insulation voltage / for AC / rated value	V	800
--	---	-----

Operating frequency • 1 / rated value • 2 / rated value	Hz	50
	Hz	60
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		Q
		Q
Operating voltage • for main current circuit • at 50 Hz / for AC • maximum • at 60 Hz / for AC • maximum • for DC • maximum	V	690
	V	690
	V	500
Operating current • at 40 °C / rated value • at 50 °C / rated value • at 60 °C / rated value • at 70 °C / rated value	A	400
	A	400
	A	372
	A	344
Continuous current / rated value	A	400
Derating temperature / for the rated value of the continuous current	°C	50

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts

0

Number of NO contacts / for auxiliary contacts

0

Short-circuit:

Adjustable response current

- of the current-dependent overload release
 - initial value
- of the non-delayed short-circuit release
 - initial value
 - final value

...

A

4,000 ...

A

4,000

Breaking capacity limit short-circuit current (Icu) / at 415 V / rated value

kA

70

Installation/mounting/dimensions:

Type of mounting

fixed mounting

Height

mm

279.5

Width

mm

183.5

Depth	mm	163.5
--------------	----	-------

Connections:

Arrangement of electrical connectors / for main current circuit		front side
Design of the electrical connection / for main current circuit		screw-type terminals
Type of the connectable conductor cross-section		
<ul style="list-style-type: none"> • for main contacts <ul style="list-style-type: none"> • with flexible busbar • solid • finely stranded / with conductor end processing • stranded • for auxiliary contacts <ul style="list-style-type: none"> • solid • finely stranded / with conductor end processing 		25 x 10 50 ... 300 mm ² 50 ... 240 mm ² 50 ... 300 mm ² 0,75 ... 1.5 mm ² 0.75 ... 1.0 mm ²

Certificates/approvals:

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL4740-2EE46-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL4740-2EE46-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 8, 2013