



SWITCH-DISCONNECTOR 125A, FRAME SIZE 2,
3-POLE FRONT OPERATING CENTER BASIC UNIT
WITHOUT HANDLE BOX TERMINAL

Similar to image

General technical details:

product brand name	SENTRON	
Product designation	Switching device	
Design of the product	3KD Switch Disconnectors	
Size of switch disconnector	2	
Number of poles	3	
Continuous current		
• rated value	A	125
• at 40 °C / rated value	A	125
• at 45 °C / rated value	A	125
• at 50 °C / rated value	A	125
• at 55 °C / rated value	A	125
• at 60 °C / rated value	A	125
• at 65 °C / rated value	A	125
• at 70 °C / rated value	A	125
• at DC / rated value	A	125
Operating current		
• at AC-21 A		
• at 400 V / maximum	A	125

• at 500 V / maximum	A	125
• at 690 V / maximum	A	125
• at AC-22 A		
• at 400 V / at 50/60 Hz / rated value / maximum	A	125
• at 500 V / at 50/60 Hz / rated value / maximum	A	125
• at 690 V / at 50/60 Hz / rated value / maximum	A	125
• at AC-23 A		
• at 400 V / at 50/60 Hz / rated value / maximum	A	125
• at 500 V / at 50/60 Hz / rated value / maximum	A	125
• at 690 V / at 50/60 Hz / rated value / maximum	A	125
• at DC-21 A		
• at 220 V / maximum / note		125 / 2
• at 440 V / rated value / maximum / note		125 / 3
• at DC-22 A		
• at 220 V / rated value / maximum / note		125 / 2
• at 440 V / rated value / maximum / note		125 / 3
• at DC-23 A		
• at 220 V / rated value / maximum / note		125 / 2
• at 440 V / rated value / maximum / note		125 / 3
Operational voltage		
• at 50/60 Hz / for AC / rated value	V	690
• with 3 current paths in series / with DC / rated value	V	440
Insulation voltage / rated value	V	1,000
Impulse voltage resistance / rated value	kV	8
Overvoltage class		III
Operating power / at AC-23 A		
• at 400 V / at 50/60 Hz / rated value	kW	55
• at 500 V / at 50/60 Hz / rated value	kW	75
• at 690 V / at 50/60 Hz / rated value	kW	110
I_{2t} value / with closed switch		
• for combination switch + fuse		
• at 400 V / maximum	A ² ·s	135,600
• at 500 V / maximum	A ² ·s	135,600
• at 690 V		
• for combination switch +gG fuse / maximum	A ² ·s	178,300
• for combination switch +aM fuse / maximum	A ² ·s	201,200
Let-through current / with closed switch		
• for combination switch + fuse		
• at 400 V / maximum permissible	A	17,900
• at 500 V / maximum permissible	A	17,900

• at 690 V		
• with combination switch +gG fuse / maximum permissible	A	17,600
• with combination switch +aM fuse / maximum permissible	A	18,700
Short-time current resistance (Icw) / limited to 1 s / rated value	kA	4
Making capacity short-circuit current (Icm) / for switch disconnector / without fuse link / rated value / minimum	kA	12
Conditional short-circuit current / with line-side fuse protection		
• at 500 V / by gG fuse / rated value	kA	100
• at 690 V / by gG fuse / rated value	kA	65
Active power loss / with conventional rated thermal current / per pole	W	4.5
Product equipment / interlock		No
Type of the driving mechanism / motor drive		No
Product extension / optional / motor drive		No
Design of the electrical connection / for main current circuit		Box terminal
Type of connectable conductor cross-sections		
• for copper conductor		
• solid		1x (2,5 ... 16mm ²)
• stranded		1x (10 ... 70 mm ²)
• finely stranded / with end sleeve		1x (2,5 ... 70mm ²)
• with flexible busbar		3x (0,8x14mm ²)
Number of connected NC contacts / for auxiliary contacts		0
Number of connected NO contacts / for auxiliary contacts		0
Number of connected changeover contacts / for auxiliary contacts		0
Product extension / auxiliary switch		Yes
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of changeover contacts / for auxiliary contacts		4
Acceptability for application / switch disconnector		Yes
Acceptability for application		
• emergency stop switch		No
• main switch		Yes
• safety cut-out switch		Yes
• maintenance/repair switch		Yes
Design of the operating mechanism		without
Mounting type		Floor mounting and snap-on mounting to 35 mm standard mounting rail
Mounting type / rail mounting		Yes
Mounting type / front mounting with 4-hole attachment		No
Mounting type / front mounting with central attachment		No

Type from device		fixed mounting
mounting position		any
Position / of switch operating mechanism		after the first pole
Design of handle		without
Width	mm	121
Height	mm	126
Depth	mm	68
Protection class IP		IP20
• on the front		IP20
• with closed switch / with cover or cable lug cover		IP20
Ambient temperature		
• during operating	°C	-25 ... +70
• during storage	°C	-50 ... +80
Degree of pollution		3
Mechanical operating cycles as operating time / typical		15,000
Electrical endurance (switching cycles)		
• at AC-23 A / at 690 V / at 50/60 Hz		1,500
• at DC-23 A		
• at 220 V		1,000
• at 440 V		1,000
Design of display		
• for switch position indicator door-coupling rotary operating mechanism		ON-OFF
Net weight	g	850
Reference code / according to DIN EN 61346-2		Q
Item designation / according to DIN EN 81346-2		Q

Certificates/approvals:

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)




<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3KD3230-2NE20-0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3KD3230-2NE20-0/all>

Tender specifications

[Dataform](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)





last change:

Apr 21, 2014