

Similar to image

CIRCUIT-BREAKER VL 250N STANDARD BREAKING  
CAPACITY ICU=55KA / 415 V AC 3 POLE,  
NON-AUTOMATIC OVERCURRENT RELEASE MAGNETIC  
IN=250A,  
RATED CURRENT II=3500A,  
SHORT-CIRCUIT II=4000A, SHORT-CIRCUIT

### General technical data:

|                                                                |     |                                |
|----------------------------------------------------------------|-----|--------------------------------|
| <b>Number of poles</b>                                         |     | 3                              |
| <b>Design of the overcurrent release</b>                       |     | M                              |
| <b>Acceptability for application</b>                           |     | non-automatic circuit-breakers |
| <b>Electrical operating cycles as operating time / typical</b> |     | 10,000                         |
| <b>Mechanical operating cycles as operating time / typical</b> |     | 20,000                         |
| <b>Active power loss / maximum</b>                             | W   | 60                             |
| <b>Product component</b>                                       |     |                                |
| • auxiliary switch                                             |     | No                             |
| • Voltage trigger                                              |     | No                             |
| • undervoltage release mechanism                               |     | No                             |
| • undervoltage release with leading contact                    |     | No                             |
| <b>Product function</b>                                        |     |                                |
| • of the thermal overload release                              |     | Without                        |
| • ground-fault protection                                      |     | No                             |
| • for zero conductors / short-circuit and overload protection  |     | No                             |
| • overload protection                                          |     | No                             |
| <b>Operating cycles / maximum</b>                              | 1/s | 120                            |
| <b>Protection class IP</b>                                     |     | IP20                           |
| <b>Protective function of the overcurrent release</b>          |     | I                              |
| <b>Impulse voltage resistance / rated value</b>                | kV  | 8                              |
| <b>Ambient temperature</b>                                     |     |                                |
| • during operating                                             |     |                                |
| • minimum                                                      | °C  | -25 ...                        |
| • maximum                                                      | °C  | 70                             |
| • during storage                                               |     |                                |
| • minimum                                                      | °C  | -40                            |
| • maximum                                                      | °C  | 50                             |

### Main circuit:

|                                                                             |    |       |
|-----------------------------------------------------------------------------|----|-------|
| <b>Insulation voltage / for AC / rated value</b>                            | V  | 800   |
| <b>Operating frequency</b>                                                  |    |       |
| • 1 / rated value                                                           | Hz | 50    |
| • 2 / rated value                                                           | Hz | 60    |
| <b>Item designation</b>                                                     |    |       |
| • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750  |    | Q     |
| • according to DIN EN 61346-2                                               |    | Q     |
| <b>Operating voltage</b>                                                    |    |       |
| • for main current circuit                                                  |    |       |
| • at 50 Hz / for AC                                                         |    |       |
| • maximum                                                                   | V  | 690   |
| • at 60 Hz / for AC                                                         |    |       |
| • maximum                                                                   | V  | 690   |
| • for DC                                                                    |    |       |
| • maximum                                                                   | V  | 500   |
| <b>Operating current</b>                                                    |    |       |
| • at 40 °C / rated value                                                    | A  | 250   |
| • at 50 °C / rated value                                                    | A  | 250   |
| • at 60 °C / rated value                                                    | A  | 232.5 |
| • at 70 °C / rated value                                                    | A  | 215   |
| <b>Continuous current / rated value</b>                                     | A  | 250   |
| <b>Derating temperature / for the rated value of the continuous current</b> | °C | 50    |

#### Auxiliary circuit:

|                                                       |  |   |
|-------------------------------------------------------|--|---|
| <b>Number of NC contacts / for auxiliary contacts</b> |  | 0 |
| <b>Number of NO contacts / for auxiliary contacts</b> |  | 0 |

#### Short-circuit:

|                                                                                                |    |           |
|------------------------------------------------------------------------------------------------|----|-----------|
| <b>Adjustable response current</b>                                                             |    |           |
| • of the current-dependent overload release                                                    |    |           |
| • initial value                                                                                |    | ...       |
| • of the non-delayed short-circuit release                                                     |    |           |
| • initial value                                                                                | A  | 3,500 ... |
| • final value                                                                                  | A  | 3,500     |
| <b>Breaking capacity limit short-circuit current (I<sub>cu</sub>) / at 415 V / rated value</b> | kA | 55        |

#### Installation/mounting/dimensions:

|                         |    |                |
|-------------------------|----|----------------|
| <b>Type of mounting</b> |    | fixed mounting |
| <b>Height</b>           | mm | 185.5          |

|              |    |       |
|--------------|----|-------|
| <b>Width</b> | mm | 104.5 |
| <b>Depth</b> | mm | 106.5 |

#### Connections:

**Arrangement of electrical connectors / for main current circuit**

front side

**Design of the electrical connection / for main current circuit**

screw-type terminals

**Type of the connectable conductor cross-section**

- for main contacts
  - with flexible busbar
  - solid
  - finely stranded / with conductor end processing
  - stranded
- for auxiliary contacts
  - solid
  - finely stranded / with conductor end processing

17 x 10 mm

25 ... 185 mm<sup>2</sup>

25 ... 120 mm<sup>2</sup>

25 ... 185 mm<sup>2</sup>

0,75 ... 1.5 mm<sup>2</sup>

0.75 ... 1.0 mm<sup>2</sup>

#### Certificates/approvals:

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/mall>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3VL3725-1DE36-0AA0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL3725-1DE36-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3725-1DE36-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**last change:**

Feb 8, 2013