

Similar to image

CIRCUIT-BREAKER VL 250N STANDARD BREAKING
CAPACITY ICU=55KA / 415 V AC 3 POLE,
MOTOR/GENERATOR PROTECTION ELECTRONIC TRIP
UNIT LCD ETU40M,
LI IN=200A, RATED CURRENT IR=80-200A,
OVERLOAD II=1,25TO11XIN,
SHORT CIRCUIT WITHOUT AUXILIARY RELEASE

General technical data:

Number of poles		3
Design of the overcurrent release		LCD ETU40M
Acceptability for application		Motor Protection
Electrical operating cycles as operating time / typical		10,000
Mechanical operating cycles as operating time / typical		20,000
Active power loss / maximum	W	60
Product component		
• auxiliary switch		No
• Voltage trigger		No
• undervoltage release mechanism		No
• undervoltage release with leading contact		No
Product function		
• of the thermal overload release		adjustable
• ground-fault protection		No
• for zero conductors / short-circuit and overload protection		No
• overload protection		Yes
Operating cycles / maximum	1/s	120
Protection class IP		IP20
Protective function of the overcurrent release		LI
Impulse voltage resistance / rated value	kV	8
Ambient temperature		
• during operating		
• minimum	°C	-25 ...
• maximum	°C	70
• during storage		
• minimum	°C	-40
• maximum	°C	50

Main circuit:		
Insulation voltage / for AC / rated value	V	800
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Service power / at AC-3		
• at 230 V / rated value	kW	36.8
• at 400 V / rated value	kW	110.8
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		Q
• according to DIN EN 61346-2		Q
Operating voltage		
• for main current circuit		
• at 50 Hz / for AC		
• maximum	V	690
• at 60 Hz / for AC		
• maximum	V	690
Operating current		
• at 40 °C / rated value	A	200
• at 50 °C / rated value	A	200
• at 60 °C / rated value	A	190
• at 70 °C / rated value	A	160
Continuous current / rated value	A	200
Derating temperature / for the rated value of the continuous current	°C	50
Auxiliary circuit:		
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Short-circuit:		
Adjustable response current		
• of the current-dependent overload release		
• initial value	A	80 ...
• final value	A	200
• of the non-delayed short-circuit release		
• initial value	A	250 ...
• final value	A	2,200
Breaking capacity limit short-circuit current (I_{cu}) / at 415 V / rated value	kA	55

Installation/mounting/dimensions:

Type of mounting		fixed mounting
Height	mm	185.5
Width	mm	104.5
Depth	mm	106.5

Connections:

Arrangement of electrical connectors / for main current circuit		front side
Design of the electrical connection / for main current circuit		screw-type terminals
Type of the connectable conductor cross-section • for main contacts • with flexible busbar • solid • finely stranded / with conductor end processing • stranded • for auxiliary contacts • solid • finely stranded / with conductor end processing		17 x 10 mm 25 ... 185 mm² 25 ... 120 mm² 25 ... 185 mm² 0,75 ... 1.5 mm² 0.75 ... 1.0 mm²

Certificates/approvals:**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL3720-1UP36-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3720-1UP36-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 8, 2013