

Pakknippel IP68 EMC Metrisk



Materiale	Forniklet messing
Lamellinsats	Polyamid PA6 V-2
Pakning	Polykloropren-Nitrilgummi CR/NBR
O-ring	Nitrilgummi NBR
Beskyttelsesgrad	IP68 - 5 bar
Temperaturområde	-20°C....+100°C
Test Standard	EN 50262 / UL 514B
VDE licens	40020901
UL / CSA-Fil	E140310
SEV licens	02.1466
EU toll statistikk kode	74199900
UNSPSC kod	39121431

Halogenfri



El-nummer	Yttergjenge	For kabel Ø mm	L mm	H mm	SW1 mm	E1 mm	Di mm	Antall/pkn
1241945	M12x1,5	3 - 6	5	25	14	15,5	6	100
1241946	M16x1,5	5 - 9	5	30	17	19	9	100
1241947	M20x1,5	9 - 13	6	33,5	22	24	13	100
1241948	M25x1,5	11 - 16	7	36,5	27	30	16	50
1241949	M32x1,5	14 - 21	8	38	34	36	21	25
1241950	M40x1,5	19 - 27	8	41	43	46	27	10
1241951	M50x1,5	24 - 35	9	49,5	55	60	35	5
1241952	M63x1,5	32 - 42	10	52,5	65	70	48	5

Rutab – Gjennomfør det smartere

Rutab AS (HK Norge)
Billingstadsletta 17
NO-1396 Billingstad
Norge
Tel: +47 35595556
Fax: +47 21075559

Rutab AB (HK Sverige)
Lerbacksgatan 2
571 38 Nässjö
Sverige
Växel: 0380 - 55 50 50
Fax: 0380 - 12303

Rutab AB
Box 11024
100 61 Stockholm
Sverige
Besöksadress:
Malmgårdsvägen 63B
Fax: 08 - 557 730 05

Rutab AB
Mörsaregatan 8
254 66 Helsingborg
Sverige
Fax: 042-15 99 40