


PE TERMINAL 1 SCREW TERMINAL GREEN-YELLOW,
7.2MM, SZ 4



Similar to image

Technical data:		
Type of mounting		DIN rail 35 mm
Length	mm	51
Color		green-yellow
Height of lowest mounting type	mm	30
Number of terminal levels		1
Number of terminal points / per terminal level		1
Product feature / PEN function		No
Combustibility class acc. to UL 94		V2
Terminal contact spacing	mm	7.2
Position / of terminal		lateral
Product component / required / connection plate		No
Ambient temperature / during operating		
• minimum	°C	-25
• maximum	°C	55
Design of the electrical connection		
• 1		screw-type terminal
• 2		screw-type terminal
Conductor cross-section that can be connected		

- solid
 - maximum
- multibrin
 - maximum
- finely stranded
 - with wire end processing
 - maximum
 - without wire end processing
 - maximum

mm ²	4
mm ²	4
mm ²	4
mm ²	4

Certificates/approvals:

General Product Approval



CSA

GOST

UL

EG-Konf.

Shipping Approval



ABS

GL

PRS

other

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-1PG01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1PG01

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 11, 2013