


INSTRUMENT ISOL. TERM. THERMOPL SCREW
TERMINAL ON BOTH ENDS W. TEST SOCKET,
8MM, SZ 6



Similar to image

Technical data:		
Type of mounting		DIN rail 35 mm
Type of longitudinal separation		sliding
Type of lateral separation		without
Length	mm	83
Color		beige
Height of lowest mounting type	mm	33
Number of terminal levels		1
Number of terminal points / per terminal level		2
Design of terminal / terminal levels linked internally		No
Operating voltage / rated value	V	600
Operating current / rated value	A	35
Combustibility class acc. to UL 94		V2
Insulation material		thermoplastic
Terminal contact spacing	mm	8
Position / of terminal		lateral
Product component		
• required / connection plate		No
• Test socket		Yes

Design of the electrical connection • 1 • 2		screw-type terminal screw-type terminal
Conductor cross-section that can be connected • solid • minimum • maximum • multibrin • minimum • maximum • finely stranded • with wire end processing • minimum • maximum • without wire end processing • minimum • maximum	mm ² mm ² mm ² mm ² mm ² mm ² mm ² mm ² mm ² mm ²	6 6 6 6 6 6 6 6

Certificates/approvals:

General Product Approval



EG-Konf.

Shipping Approval



GL



PRS

other

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-1MH15/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1MH15

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 11, 2013