


TWO-TIER TERMINAL THERMOPLASTIC CONNECTION
ON BOTH ENDS DIODE TERMINAL,
6.5MM SZ 4



Similar to image

Technical data:		
Design tested acc. to type of protection / EEx e		No
Component type		diode
Length	mm	64
Height of lowest mounting type	mm	45
Type of mounting		DIN rail 35 mm
Number of terminal levels		2
Number of terminal points / per terminal level		2
Design of terminal / terminal levels linked internally		No
Operating voltage / rated value	V	250
Operating current / rated value	A	32
Combustibility class acc. to UL 94		others
Color		grey
Insulation material		others
Terminal contact spacing	mm	6.5
Position / of terminal		top
Product component / required / connection plate		No
Design of the electrical connection		
• 1		screw-type terminal

• 2

Conductor cross-section that can be connected

- solid
- multibrin
- finely stranded
 - with wire end processing
 - without wire end processing

		screw-type terminal
mm ²	4 ... 4	
mm ²	4 ... 4	
mm ²	4 ... 4	
mm ²	4 ... 4	

Certificates/approvals:

General Product Approval	Declaration of Conformity	Shipping Approval	other
 GOST	 UL	 EG-Konf.	 PRS
			Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-6EG20/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-6EG20

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 11, 2013