

AUXILIARY SW. WITH TEST BUTTON 2NO FOR MCB 5SL, 5SY, 5SP, ON-OFF-SW. 5TL1 RCBO 5SU1, RCD 5SV



Model	
Product brand name	SETRON
Product designation	Auxiliary current switch
Design of the product	Mountable
Design of the product / factory mounted	No
Control current	
Type of voltage / of control voltage	AC/DC
Product details	
Product extension	Auxiliary current switch
can be mounted	RCBO and miniature circuit breaker
Number	
Number of fault signal contacts	0
Number of NC contacts	0
Number of NO contacts	2
Number of CO contacts	0
Mechanical Design	
Height	90 mm

Width	9 mm
Depth	70 mm
Number of width units	0.5
Net weight	49 g
Equipment marking	SF
• acc. to DIN EN 81346-2	

Declaration of Conformity



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3011-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3011-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3011-2

CAX-Online-Generator


<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



13 23



14 24

