



Model	
product brandname	SENTRON
Product designation	accessories
Connections according IEC	
Connectable conductor cross-section	
• for copper cable / finely stranded / minimum	35 mm ²
• for copper cable / finely stranded / maximum	150 mm ²
• for copper cable / finely stranded / with core end processing / minimum	35 mm ²
• for copper cable / finely stranded / with core end processing / maximum	150 mm ²
• for copper cable / stranded / minimum	35 mm ²
• for copper cable / stranded / maximum	185 mm ²
• for aluminum cable / stranded / minimum	35 mm ²
• for aluminum cable / stranded / maximum	185 mm ²
Wire stripping length	20 mm
Connections according UL	
Connectable conductor cross-section	

• for copper-cable / multi-stranded / minimum	35
• for copper-cable / multi-stranded / maximum	185
• for copper-cable / finely stranded / minimum	35
• for copper-cable / finely stranded / maximum	150
• for copper-cable / finely stranded / with insulated conductor end processing / minimum	35
• for copper-cable / finely stranded / with insulated conductor end processing / maximum	150
• for aluminum-cable / multi-stranded / minimum	35
• for aluminum-cable / multi-stranded / maximum	185

Certificates

General Product Approval	EMC	Declaration of Conformity	Test Certificates	other
		 EG-Konf.	Typprüfbescheinigung/Werkszeugnis	Sonstige

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9254-0JB12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9254-0JB12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9254-0JB12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

06/05/2017