



Model	
product brandname	SENTRON
Product designation	accessories
Connections according IEC	
Connectable conductor cross-section	
• for copper cable / solid / minimum	1.5 mm²
• for copper cable / solid / maximum	16 mm²
• for copper cable / finely stranded / minimum	1.5 mm²
• for copper cable / finely stranded / maximum	50 mm²
• for copper cable / finely stranded / with core end processing / minimum	1.5 mm²
• for copper cable / finely stranded / with core end processing / maximum	50 mm²
• for copper cable / stranded / minimum	1.5 mm²
• for copper cable / stranded / maximum	70 mm²
Type of connectable conductor cross-sections / of the laminated conductor rails	
• minimum	1 9 x 9 mm x 0.8 mm

• maximum	3 6 x 13 mm x 0.5 mm
Wire stripping length	12 mm
Tightening torque	
• at usage of copper-cables / single-wire	<= 16 mm ² : 5 Nm
• at usage of copper-cables / multi-stranded	<= 16 mm ² : 5 Nm, >= 25 mm ² : 8 Nm
• at usage of copper-cables / finely stranded	<= 16 mm ² : 5 Nm, >= 25 mm ² : 8 Nm

Connections according UL

Wire stripping length	0.5 in
Connectable conductor cross-section	
• for copper-cable / single-wire / minimum	14 AWG
• for copper-cable / single-wire / maximum	10 AWG
• for copper-cable / multi-stranded / minimum	14 AWG
• for copper-cable / multi-stranded / maximum	3/0 AWG
• for copper-cable / finely stranded / minimum	14 AWG
• for copper-cable / finely stranded / maximum	3/0 AWG
• for copper-cable / finely stranded / with insulated conductor end processing / minimum	14 AWG
• for copper-cable / finely stranded / with insulated conductor end processing / maximum	3/0 AWG
Tightening torque / at usage of copper-cables	
• single-wire	<= 10 AWG: 45 lb-in
• multi-stranded	<= 6 AWG: 45 lb-in, >= 4 AWG: 70 lb-in
• finely stranded	<= 6 AWG: 45 lb-in, >= 4 AWG: 70 lb-in

Certificates

General Product Approval	EMC	Declaration of Conformity	Test Certificates	other
--------------------------	-----	---------------------------	-------------------	-------



[Typprüfbescheinigung/Werkszeugnis](#)

[Sonstige](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9154-0JA11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3VA9154-0JA11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9154-0JA11

CAX-Online-Generator

<http://www.siemens.com/cax>



last modified:

06/05/2017