



Model	
product brandname	SENTRON
Product designation	accessories
Connections according IEC	
Thickness / of the busbar / minimum	0 mm
Width / of the busbar / maximum	17 mm
Thickness / of the busbar / maximum	6.5 mm
Connetctions according UL	
Width / of current bar / maximum	0.7 in
Thickness / of current bar / minimum	0 in
Thickness / of current bar / maximum	0.25 in
Certificates	

General Product Approval	EMC	Declaration of Conformity	Test Certificates	other
--------------------------	-----	---------------------------	-------------------	-------



[Typprüfbescheinigung/Werkszeugnis](#)

[Sonstige](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9113-0QA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9113-0QA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)





http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9113-0QA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

06/05/2017