

BUSBAR ADAPTER MCCB, 160 A 60 MM BUSBAR SYSTEM FOR
3VA10/11,VA50/51 200 X 77 MM



Model	
product brandname	SENTRON
Design of the product	Accessories
Insulation voltage / rated value	800 V
Surge voltage resistance / rated value	6 kV
Dissipation	
Power loss [W]	12 W
Power loss [W]	10 W
• for rated value of the current / at AC / in hot operating state / per pole	
• maximum	
Current / at AC / rated value	160 A
Operating voltage / at AC / rated value	690 V
Height	200 mm
Width	77 mm
Busbar center-to-center spacing	60 mm
Net weight	569 g

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------	---------------------------	-------------------	-------------------



[Special Test Certificate](#)

[Miscellaneous](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AU01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AU01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AU01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



