

BUSBAR ADAPTER MCCB, 250 A 60 MM BUSBAR SYSTEM FOR  
3VA12/20/21/22/52/61/62 241 X 105 MM



| Model                                                                        |             |
|------------------------------------------------------------------------------|-------------|
| product brandname                                                            | SENTRON     |
| Design of the product                                                        | Accessories |
| Insulation voltage / rated value                                             | 800 V       |
| Surge voltage resistance / rated value                                       | 6 kV        |
| Dissipation                                                                  |             |
| Power loss [W]                                                               | 18 W        |
| Power loss [W]                                                               | 18 W        |
| • for rated value of the current / at AC / in hot operating state / per pole |             |
| • maximum                                                                    | 18 W        |
| Current / at AC / rated value                                                | 250 A       |
| Operating voltage / at AC / rated value                                      | 690 V       |
| Height                                                                       | 240 mm      |
| Width                                                                        | 105 mm      |
| Busbar center-to-center spacing                                              | 60 mm       |
| Net weight                                                                   | 1 231 g     |

| General Product Approval                                                                | Declaration of Conformity                                                                | Test Certificates                                                                             | Shipping Approval                                                                                                                                                       |
|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>UL | <br>EAC | <br>EG-Konf. | <a href="#">Special Test Certificate</a><br><a href="#">Miscellaneous</a><br><br>PRS |

## Shipping Approval



## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AP03>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AP03>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1213-4AP03](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AP03)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



