



CIRCUIT BREAKER 3VA2 IEC FRAME 250 BREAKING
CAPACITY CLASS M ICU=55KA @ 415 V 4POLE,
LINE PROTECTION ETU350, LSI,
IN=160A OVERLOAD PROTECTION IR=64A ...160A
SHORT CIRCUIT PROTECTION ISD=1,5... 10 X IR,
II=12 X IN NEUTRAL PROTECTION
ADJUSTABLE(OFF,50%,100%) BUSBAR CONNECTION

Similar to image

General technical data:		
product brand name		SETRON
Product designation		Molded Case Circuit Breakers
Acceptability for application		system protection
Design of the product		Line Protection
Product function	• communication function	No
	• other measurement function	No
Product component / display		No
Design of the overcurrent release		ETU350
Protective function of the overcurrent release		LSI
Product property / for zero conductors / up/downgradable / short-circuit and overload protection		No
Continuous current / rated value	A	160
Operating voltage		
	• at 50/60 Hz / for AC / rated value	V 690
Insulation voltage / rated value	V	800
Number of poles		4
Active power loss / maximum	W	48

Switching capacity class of the circuit breaker		M
Protection class IP / on the front		IP40

Motor rating data:

Product function / phase disturbance recognition		No
--	--	----

Schaltvermögen:

Breaking capacity limit short-circuit current (I_{cu}) • at 240 V / rated value • at 415 V / rated value • at 690 V / rated value	kA kA kA	85 55 3
Breaking capacity operating short-circuit current (I_{cs}) • at 240 V / rated value • at 415 V / rated value • at 690 V / rated value	kA kA kA	85 55 3
Ultimate short-circuit current making capacity (I_{cm}) • at 240 V / rated value • at 415 V / rated value • at 690 V / rated value	kA kA kA	187 121 4.5

Overcurrent Release:

Adjustable response current • of the current-dependent overload release • of the non-delayed short-circuit release / initial value	A A	0.394 ... 1 12
Adjustable response current • of the short-time delayed short-circuit release	A	1.5 ... 10
Settable delay / of the S-trip • with I_{2t} characteristic	s	0.02 ... 0.4
Settable current response value / of I-trip / end value	A	12

Connections:

Design of the electrical connection • for main current circuit		Lug Terminal
---	--	--------------

Control circuit:

Number of changeover contacts • for auxiliary contacts		0
Product component • undervoltage release mechanism • Voltage trigger • undervoltage release with leading contact • trip indicator		No No No No

Manufacturer article number

- 3 of the integrated auxiliary switch /alarm switch
- of integrated auxiliary trip

Ambient conditions:**Ambient temperature**

- during operating
- during storage

°C	-25 ... +70
°C	-40 ... +80

Dimensions and weights:

Width	mm	140
Height	mm	181
Depth	mm	107
Net weight	g	3,080

Lebensdauer:

Mechanical operating cycles as operating time / typical	20,000
Reference code / according to DIN EN 61346-2	Q

Certificates/approvals:**Declaration of Conformity****Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2216-5HN42-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3VA2216-5HN42-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2216-5HN42-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

May 14, 2014