SIEMENS

Product data sheet 3VA9267-0HA10

MOTOR OPERATOR 24-60 V DC ACCESSORY FOR: 3VA2 100/160/250



Similar to image

Technical data:		
Accessories		Motorized operating mechanism (MO)
Type of the driving mechanism		motorized operating mechanism
Ambient temperature		
during storage	°C	-40 +80
during operating	°C	-25 +70
Control supply voltage		
• for DC / rated value	V	24 60
Type of current / for actuation		AC/DC
Break time / typical	s	800
Make time / typical	s	800
IP degree of protection / with closed switch		
• without cover or cable lug cover		IP20, with masking frame IP30
Section de conducteur raccordable		
• solid	mm²	1.5 2.5
• multibrin	mm²	1.5 2.5
• finely stranded		
• with wire end processing	mm²	1.5 2.5
Starting torque	N⋅m	0.36 0.44

mm	7
ms	100
1/h	120
	No
V-A	250
	0.85 1.1
	1.1 0.85
	0.85 1.26
	ms 1/h

Certificates/approvals:

Declaration of Conformity

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA9267-0HA10

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


http://support.automation.siemens.com/WW/view/en/3VA9267-0HA10/all


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9267-0HA10}$

CAx-Online-Generator

http://www.siemens.com/cax





last change: Apr 21, 2014