



CIRCUIT BREAKER 3VA2 IEC FRAME 160 BREAKING CAPACITY CLASS M ICU=55KA @ 415 V 4POLE, LINE PROTECTION ETU350, LSI, IN=40A OVERLOAD PROTECTION IR=16A ...40A SHORT CIRCUIT PROTECTION ISD=1,5... 10 X IR, II=12 X IN NEUTRAL PROTECTION ADJUSTABLE(OFF,100%) CABLE CONNECTION

Similar to image

General technical data:		
product brand name		SENTRON
Product designation		Molded Case Circuit Breakers
Acceptability for application		system protection
Design of the product		Line Protection
Product function		
• communication function		No
• other measurement function		No
Product component / display		No
Design of the overcurrent release		ETU350
Protective function of the overcurrent release		LSI
Product property / for zero conductors / up/downgradable / short-circuit and overload protection		No
Continuous current / rated value	A	40
Operating voltage		
• at 50/60 Hz / for AC / rated value	V	690
Insulation voltage / rated value	V	800
Number of poles		4
Active power loss / maximum	W	25.5

Switching capacity class of the circuit breaker		M
Protection class IP / on the front		IP40

Motor rating data:

Product function / phase disturbance recognition

No

Schaltvermögen:

Breaking capacity limit short-circuit current (Icu)

- at 240 V / rated value
- at 415 V / rated value
- at 690 V / rated value

kA 85
kA 55
kA 2.5

Breaking capacity operating short-circuit current (Ics)

- at 240 V / rated value
- at 415 V / rated value
- at 690 V / rated value

kA 85
kA 55
kA 2.5

Ultimate short-circuit current making capacity (Icm)

- at 240 V / rated value
- at 415 V / rated value
- at 690 V / rated value

kA 187
kA 121
kA 3.75

Overcurrent Release:

Adjustable response current

- of the current-dependent overload release
- of the non-delayed short-circuit release / initial value

A 0.4 ... 1
A 12

Adjustable response current

- of the short-time delayed short-circuit release

A 1.5 ... 10

Settable delay / of the S-trip

- with I2t characteristic

s 0.02 ... 0.4

Settable current response value / of I-trip / end value

A 12

Connections:

Design of the electrical connection

- for main current circuit

Frame terminal

Control circuit:

Number of changeover contacts

- for auxiliary contacts

0

Product component

- undervoltage release mechanism
- Voltage trigger
- undervoltage release with leading contact
- trip indicator

No
No
No
No

Manufacturer article number

- 3 of the integrated auxiliary switch /alarm switch
- of integrated auxiliary trip

Ambient conditions:**Ambient temperature**

- during operating
- during storage

°C	-25 ... +70
°C	-40 ... +80

Dimensions and weights:

Width	mm	140
Height	mm	181
Depth	mm	107
Net weight	g	3,125

Lebensdauer:

Mechanical operating cycles as operating time / typical	20,000
Reference code / according to DIN EN 61346-2	Q

Certificates/approvals:**Declaration of Conformity****Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2140-5HN46-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3VA2140-5HN46-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2140-5HN46-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

May 14, 2014