



CIRCUIT BREAKER 3VA2 IEC FRAME 160 BREAKING
CAPACITY CLASS M ICU=55KA @ 415 V 4POLE,
LINE PROTECTION ETU350, LSI,
IN=100A OVERLOAD PROTECTION IR=40A ...100A
SHORT CIRCUIT PROTECTION ISD=1,5... 10 X IR,
II=12 X IN NEUTRAL PROTECTION
ADJUSTABLE(OFF,50%,100%) BUSBAR CONNECTION

Similar to image

General technical data:		
product brand name		SETRON
Product designation		Molded Case Circuit Breakers
Acceptability for application		system protection
Design of the product		Line Protection
Product function	• communication function	No
	• other measurement function	No
Product component / display		No
Design of the overcurrent release		ETU350
Protective function of the overcurrent release		LSI
Product property / for zero conductors / up/downgradable / short-circuit and overload protection		No
Continuous current / rated value	A	100
Operating voltage		
	• at 50/60 Hz / for AC / rated value	V 690
Insulation voltage / rated value	V	800
Number of poles		4
Active power loss / maximum	W	25.5

Switching capacity class of the circuit breaker		M
Protection class IP / on the front		IP40

Motor rating data:

Product function / phase disturbance recognition		No
--	--	----

Schaltvermögen:

Breaking capacity limit short-circuit current (I_{cu})

• at 240 V / rated value	kA	85
• at 415 V / rated value	kA	55
• at 690 V / rated value	kA	2.5

Breaking capacity operating short-circuit current (I_{cs})

• at 240 V / rated value	kA	85
• at 415 V / rated value	kA	55
• at 690 V / rated value	kA	2.5

Ultimate short-circuit current making capacity (I_{cm})

• at 240 V / rated value	kA	187
• at 415 V / rated value	kA	121
• at 690 V / rated value	kA	3.75

Overcurrent Release:

Adjustable response current

• of the current-dependent overload release	A	0.4 ... 1
• of the non-delayed short-circuit release / initial value	A	12

Adjustable response current

• of the short-time delayed short-circuit release	A	1.5 ... 10
---	---	------------

Settable delay / of the S-trip

• with I _{2t} characteristic	s	0.02 ... 0.4
---------------------------------------	---	--------------

Settable current response value / of I-trip / end value

A	12
---	----

Connections:

Design of the electrical connection

• for main current circuit		Lug Terminal
----------------------------	--	--------------

Control circuit:

Number of changeover contacts

• for auxiliary contacts		0
--------------------------	--	---

Product component

• undervoltage release mechanism		No
• Voltage trigger		No
• undervoltage release with leading contact		No
• trip indicator		No

Manufacturer article number

- 3 of the integrated auxiliary switch /alarm switch
- of integrated auxiliary trip

Ambient conditions:**Ambient temperature**

- during operating
- during storage

°C -25 ... +70

°C -40 ... +80

Dimensions and weights:**Width**

mm 140

Height

mm 181

Depth

mm 107

Net weight

g 2,930


Lebensdauer:**Mechanical operating cycles as operating time / typical**

20,000

Reference code / according to DIN EN 61346-2

Q

Certificates/approvals:**Declaration of Conformity****Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2110-5HN42-0AA0>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3VA2110-5HN42-0AA0/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2110-5HN42-0AA0**CAX-Online-Generator**<http://www.siemens.com/cax>



last change:

May 14, 2014