


Pakknippel Messing IP68 Ex e Metrisk



Materiale	Forniklet messing
Lamellinsats	Polyamid PA6 V-2
Pakning	Polykloropren-Nitrilgummi CR/NBR
O-ring	Nitrilgummi NBR
Dammskydd	Polyetylen PE-LD
Beskyttelsesgrad	IP68 - 5 bar
Temperaturområde	-20°C.....+80°C
Utrustningsgruppe	II
Kategori / Zon	2G og 2D / 1, 2, 21, 22
Type av beskyttelse	Ex e, tennsikker utførelse / Ex td A21, Protection by enclosures
Test Standard	EN 60079-0 / EN 60079-7 / EN 61241-0 / EN 61241-1
EG Type sertifikat	DMT 99 ATEX E016
Halogenfri	

El-nummer	Yttergjenge	For kabel Ø mm	L mm	H mm	SW1 mm	E1 mm	Antall/pkn
1243680	M12x1,5	3 - 6	5	25	14	15,5	100
1243681	M12x1,5	3 - 6,5	5	24	14	15,5	100
1243682	M16x1,5	5 - 9	5	29	17	19	100
1243683	M20x1,5	9 - 13	6	33	22	24	100
1243684	M20x1,5	6 - 12	6	31	22	24	100
1243685	M25x1,5	11 - 16	7	36,5	27	30	50
1243686	M32x1,5	14 - 21	8	38	34	36	25
1243687	M40x1,5	19 - 27	8	41	43	46	10
1243688	M50x1,5	24 - 35	9	47,5	55	60	5
1243689	M63x1,5	32 - 42	10	54,5	65	70	5
1243690	M63x1,5	38 - 48	10	54,5	65	70	5