




CIRCUIT-BREAKER VL 160H HIGH BREAKING CAPACITY ICU= 70KA, 415V AC 4 POLE, LINE PROTECTION OVERCURRENT RELEASE TM, LI IN= 125A, RATED CURRENT IR= 100...125A, OVERLOAD II= 625...1250A, SHORT-CIRCUIT N PROTECTED (100%)

Model	
Type of the driving mechanism / motor drive	No
Design of the overcurrent release	TM
General technical data	
Number of poles	4
Size of the circuit-breaker	3VL2
Electrical endurance (switching cycles) / typical	10 000
Usage category	A
Performance class for circuit breaker	N
Mechanical service life (switching cycles) / typical	20 000
Reference identifier / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
Operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
Insulation voltage	
• rated value	800 V
• at AC / rated value	800 V

Surge voltage resistance / rated value	8 kV
Protection class	
Protection class IP	IP20
Protective function of the overcurrent release	LIN
Dissipation	
Power loss [W]	
• maximum	36 W
Electricity	
Operating current / at 45 °C / rated value	125 A
Continuous current / rated value	125 A
Derating temperature / for the rated value of the continuous current	50 °C
Adjustable pick-up value current	
• of the current-dependent overload release / Full-scale value	125 A
• of instantaneous short-circuit trip unit / initial value	625 A
• of instantaneous short-circuit trip unit / Full-scale value	1 250 A
Main circuit	
Operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
Operating voltage	
• rated value / maximum	690 V
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
• for main current circuit / at DC / maximum	500 V
Operating current	
• at 40 °C / rated value	125 A
• at 50 °C / rated value	125 A
• at 55 °C / rated value	116.3 A
• at 60 °C / rated value	116.3 A
• at 65 °C / rated value	107.5 A
• at 70 °C / rated value	107.5 A
Suitability	
Suitability for use	system protection
Adjustable parameters	

Adjustable pick-up value current / of the current-dependent overload release / initial value	100 A
Product details	
Product component	
• Trip indicator	No
• Auxiliary switch	No
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
Product extension / optional / motor drive	Yes
Product function	
Product function	
• of thermal overload trip unit	adjustable
• Ground fault protection	No
• for neutral conductors / Short-circuit and overload proof	Yes
• Overload protection	Yes
Short circuit	
Operational short-circuit current breaking capacity (Ics)	
• at 240 V / rated value	75 kA
• at 415 V / rated value	70 kA
• at 500 V / rated value	30 kA
• at 690 V / rated value	6 kA
Maximum short-circuit current breaking capacity (Icu)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	70 kA
• at 440 V / rated value	50 kA
• at 480 V / acc. to NEMA / rated value	50 kA
• at 500 V / rated value	40 kA
• at 600 V / acc. to NEMA / rated value	12 kA
• at 690 V / rated value	12 kA
Connections	
Arrangement of electrical connectors / for main current circuit	front side
Type of electrical connection / for main current circuit	box terminals
Mechanical Design	
Height	174.5 mm
Width	139.5 mm
Depth	106.5 mm
Mounting type	fixed mounting

Certificates

Certificate of suitability	IEC, high switching capacity (H)
Reference identifier	Q
• acc. to DIN EN 61346-2	

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



CCC

[Miscellaneous](#)

[TSE](#)

[KC](#)



C-Tick



EG-Konf.

Test Certificates	Shipping Approval	other
-------------------	-------------------	-------

[Special Test Certificate](#)



LRS



RINA



RMRS

[Confirmation](#)

[Environmental Confirmations](#)

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2712-2EM43-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL2712-2EM43-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2712-2EM43-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>