

SETRON, measuring instrument, 7KT PAC1600, LCD, L-L: 400 V, L-N: 230 V, 80 A, Standard rail device, 3-phase, Modbus RTU/ASCII + MID, apparent / active / reactive energy



Model	
Product brand name	SETRON
Design of the product	basic
Product type designation	Measuring instrument
Type of measured value detection	complete
General technical data	
Operating mode for measured value detection	Yes No No
• automatic line frequency detection	
• set at 50 Hz	
• set to 60 Hz	No
Voltage curve	Sinusoidal or distorted
Measurable line frequency / initial value	45 Hz
Measurable line frequency / Full-scale value	66 Hz
Measuring procedure / for voltage measurement	TRMS
Supply voltage	
Type of voltage / of the supply voltage	self-powered
Consumed active power	1 W
• without expansion module / typical	

Protection class	
Protection class IP	
• on the front	IP40
• Rear side	IP20
Electricity	
Measurable current / 2 / at AC / Rated value	80 A
Suitability	
Suitability for operation	Standard mounting rail device
Product function	
Product function	
• reactive power measurement	Yes
• frequency measurement	Yes
• voltage measurement	Yes
• Current measurement	Yes
• active power measurement	Yes
Display and operation	
Design of the display	LCD
Number of keys	3
Communication	
Transfer rate	
• minimum	1 200 kbit/s
• maximum	38 400 kbit/s
Inputs Outputs	
Input voltage / at digital input	
• initial value for signal<1>-recognition	85 V
• at DC / maximum	240 V
• Full-scale value for signal<0> recognition	240 V
Number of digital outputs	0
Number of digital inputs	1
Type of switching output	solid state
Operating conditions for digital inputs / external voltage supply	Yes
Measuring inputs	
Measurable supply voltage	
• between (PE)N and L / at AC / minimum	187 V
• between (PE)N and L / at AC / maximum	264 V
• between (PE)N and L / at AC / maximum rated value	230 V
• between the outer conductors / at AC / maximum rated value	400 V

Measuring category / for voltage measurement	CATIII
Continuous current / at AC / maximum permissible	80 A
Measuring category / for current measurement	CATIII
Relative measurable current / at AC	
• minimum	0.9 %
• maximum	100 %
Apparent power consumption / for current measurement	
• with measuring range 5 A / per phase	2.5 V·A
Measuring procedure / for current measurement	TRMS
Measurable current / 1 / at AC / Rated value	80 A

Connections

Type of electrical connection	
• at the measurement inputs for voltage	screw-type terminals
• at the measurement inputs for current	screw-type terminals

Mechanical Design

Height	90 mm
Width	71.6 mm
Depth	63 mm
Mounting position	any
Mounting type / panel mounting	No
Net weight	381 g

Environmental conditions

Degree of pollution	2
Installation altitude / at height above sea level / maximum	2 000 m
Relative humidity / at 25 °C / without condensation / during operation	
• maximum	80 %
Ambient temperature	
• during operation / minimum	-25 °C
• during operation / maximum	55 °C
• during storage / minimum	-25 °C
• during storage / maximum	70 °C

Certificates

Certificate of suitability	
• Approval Russia	Yes

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KT1666>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KT1666>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KT1666

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>