

Output coupler with plug-in relay, 1 CO, hard gold-plated
Screw terminal 230 V AC/DC Enclosure width 6.2 mm
Thermal current 6 A



Figure similar

Article number		
Product brand name		SIRIUS
Product category		SIRIUS 3RQ3 coupling relays in slim design
Product designation		Coupling relays with plug-in relay
Design of the product		Output coupling links
Product type designation		3RQ3

General technical data		
Display version LED		Yes
Product component		
• Relay output		Yes
• semi-conductor output		No
Consumed active power	W	1
Insulation voltage		
• for overvoltage category III according to IEC 60664		
— with degree of pollution 3 rated value	V	300
Surge voltage resistance rated value	kV	4
maximum permissible voltage for safe isolation		

• between control and auxiliary circuit	V	300
Percental drop-out voltage related to the input voltage	%	10
Protection class IP		IP20
Shock resistance		
• acc. to IEC 60068-2-27		sinusoidal half-wave 15g / 11 ms
Vibration resistance		
• acc. to IEC 60068-2-6		6 ... 150 Hz: 2 g
Operating frequency maximum	1/h	72 000
Switching behavior		monostable
Mechanical service life (switching cycles)		
• typical		10 000 000
Electrical endurance (switching cycles)		
• at AC-15 at 230 V typical		100 000
Thermal current	A	6
Equipment marking		
• acc. to DIN EN 61346-2		K
• acc. to DIN EN 81346-2		K

Control circuit/ Control

Control supply voltage at AC		
• at 50 Hz rated value	V	230
• at 60 Hz rated value	V	230
Control supply voltage at DC		
• rated value	V	230
Operating range factor control supply voltage rated value at DC		
• initial value		0.8
• Full-scale value		1.1
Operating range factor control supply voltage rated value at AC at 50 Hz		
• initial value		0.8
• Full-scale value		1.1
Operating range factor control supply voltage rated value at AC at 60 Hz		
• initial value		0.8
• Full-scale value		1.1
Off-delay time	ms	19
Closing delay		
• at AC	ms	12
• at DC	ms	8
Opening delay		
• at AC	ms	20

• at DC	ms	18
Design of the relay operating mechanism		poled
Product component Plug-in socket		Yes

Short-circuit protection

Design of the fuse link		
• for short-circuit protection of the auxiliary switch required		fuse gG: 4 A

Auxiliary circuit

Type of switching contact		Changeover contact
Material of switching contacts		AgSnO2-HTV
Number of CO contacts		
• for auxiliary contacts		1
Operating current of auxiliary contacts at AC-15		
• at 24 V	A	3
• at 250 V	A	3
Operating current of auxiliary contacts at DC-13		
• at 24 V	A	1
• at 125 V	A	0.2
• at 250 V	A	0.1
Contact reliability of auxiliary contacts		one incorrect switching operation of 100 million switching operations (5 V, 1 mA)

Main circuit

Type of voltage		AC/DC
------------------------	--	-------

Inputs/ Outputs

Property of the output Short-circuit proof		No
---	--	----

Outputs

Ampacity of the output relay at AC-15		
• at 250 V at 50/60 Hz	A	3
Ampacity of the output relay at DC-13		
• at 24 V	A	1
• at 125 V	A	0.2
• at 250 V	A	0.1

Electromagnetic compatibility

EMC emitted interference		
• acc. to IEC 60947-1		ambience A (industrial sector)
EMI immunity		
• acc. to IEC 60947-1		corresponds to degree of severity 3
Conducted interference		
• due to burst acc. to IEC 61000-4-4		2 kV

• due to conductor-earth surge acc. to IEC 61000-4-5		2 kV
• due to conductor-conductor surge acc. to IEC 61000-4-5		1 kV
Field-bound parasitic coupling acc. to IEC 61000-4-3		10 V/m
Electrostatic discharge acc. to IEC 61000-4-2		6 kV contact discharge / 8 kV air discharge

Display

Display version		
• as status display by LED		LED green

Connections/Terminals

Product function		
• removable terminal		No
Type of electrical connection		
• for auxiliary and control current circuit		screw-type terminals
Wire length		
• at AC maximum	m	500
• at DC maximum	m	1 000
Type of connectable conductor cross-sections		
• solid		1x (0.25 ... 2.5 mm ²)
• finely stranded with core end processing		1x (0.25 ... 1.5 mm ²)
• at AWG conductors solid		1 x (20 ... 14)
Connectable conductor cross-section		
• solid	mm ²	0.25 ... 2.5
• finely stranded with core end processing	mm ²	0.25 ... 1.5
AWG number as coded connectable conductor cross section		
• solid		20 ... 14
Tightening torque		
• with screw-type terminals	N·m	0.5 ... 0.6

Installation/ mounting/ dimensions

Mounting position		any
Mounting type		snap-on mounting
Height	mm	93
Width	mm	6.2
Depth	mm	76
Required spacing		
• with side-by-side mounting		
— forwards	mm	0
— Backwards	mm	0
— upwards	mm	0
— downwards	mm	0

- at the side
- for grounded parts
 - forwards
 - Backwards
 - upwards
 - at the side
 - downwards
- for live parts
 - forwards
 - Backwards
 - upwards
 - downwards
 - at the side

mm	0
mm	0
mm	0
mm	0
mm	0
mm	0
mm	0
mm	0
mm	0
mm	0
mm	0

Ambient conditions

Installation altitude at height above sea level		
• maximum	m	2 000
Ambient temperature		
• during operation	°C	-25 ... +60
• during storage	°C	-40 ... +85
• during transport	°C	-40 ... +85
Relative humidity		
• during operation	%	10 ... 95

Certificates/approvals

General Product Approval	Declaration of Conformity	other
 CCC	 EAC	 EG-Konf.



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ3118-1AF01>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ3118-1AF01>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3118-1AF01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ3118-1AF01&lang=en





last modified:

07/24/2017