

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



Powering Business Worldwide

PLHT-C63/4 - Miniature circuit breaker (MCB), 63A, 4p, C-Char, AC



248090 PLHT-C63/4

[Overview](#) [Specifications](#) [Resources](#)



248090 PLHT-C63/4

Miniature circuit breaker (MCB), 63A, 4p, C-Char, AC

EL-Nummer (Norway)

0001609535

Miniature circuit breaker (MCB) PLHT, 4 pole, Tripping characteristic: C, Rated current In: 63 A, Rated switching capacity according to IEC/EN 60947-2, Switchgear for industrial and advanced commercial applications

- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)

Delivery program

Basic function

Miniature circuit-breakers

Number of poles

4 pole

Tripping characteristic

C

Application

Switchgear for industrial and advanced commercial applications

Rated current [I_n]

63 A

Rated switching capacity acc. to IEC/EN 60947-2 [I_{cu}]

25 kA

Product range

PLHT

Technical data

Electrical

Rated switching capacity acc. to IEC/EN 60947-2 [I_{cu}]

25 kA

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_b]

63 A

Heat dissipation per pole, current-dependent [P_{id}]

0 W
 Equipment heat dissipation, current-dependent [P_{id}]
 20.8 W
 Static heat dissipation, non-current-dependent [P_{vs}]
 0 W
 Heat dissipation capacity [P_{diss}]
 0 W
 Operating ambient temperature min.
 -25 °C
 Operating ambient temperature max.
 +55 °C
 linear, per +1 °C, results in a 0.35% reduction of current carrying capacity
 IEC/EN 61439 design verification
 10.2 Strength of materials and parts 10.2.2 Corrosion resistance
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.5 Lifting
 Does not apply, since the entire switchgear needs to be evaluated.
 10.2 Strength of materials and parts 10.2.6 Mechanical impact
 Does not apply, since the entire switchgear needs to be evaluated.
 10.2 Strength of materials and parts 10.2.7 Inscriptions
 Meets the product standard's requirements.
 10.3 Degree of protection of ASSEMBLIES
 Does not apply, since the entire switchgear needs to be evaluated.
 10.4 Clearances and creepage distances
 Meets the product standard's requirements.
 10.5 Protection against electric shock
 Does not apply, since the entire switchgear needs to be evaluated.
 10.6 Incorporation of switching devices and components
 Does not apply, since the entire switchgear needs to be evaluated.
 10.7 Internal electrical circuits and connections
 Is the panel builder's responsibility.
 10.8 Connections for external conductors
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.2 Power-frequency electric strength
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.3 Impulse withstand voltage
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
 Is the panel builder's responsibility.
 10.10 Temperature rise
 The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
 10.11 Short-circuit rating
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.
 10.12 Electromagnetic compatibility
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.
 10.13 Mechanical function
 The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)
 Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014])
 Release characteristic
 C
 Number of poles (total)
 4
 Number of protected poles
 4

Rated current
63 A
Rated voltage
400 V
Rated insulation voltage U_i
440 V
Rated impulse withstand voltage U_{imp}
4 kV
Rated short-circuit breaking capacity I_{cn} EN 60898 at 230 V
0 kA
Rated short-circuit breaking capacity I_{cn} EN 60898 at 400 V
0 kA
Rated short-circuit breaking capacity I_{cu} IEC 60947-2 at 230 V
25 kA
Rated short-circuit breaking capacity I_{cu} IEC 60947-2 at 400 V
25 kA
Voltage type
AC
Frequency
50 - 60 Hz
Current limiting class
3
Suitable for flush-mounted installation
No
Concurrently switching N-neutral
Yes
Over voltage category
3
Pollution degree
2
Additional equipment possible
Yes
Width in number of modular spacings
6
Built-in depth
75 mm
Degree of protection (IP)
IP20
Ambient temperature during operating
-25 - 55 °C
Connectable conductor cross section multi-wired
2.5 - 50 mm²
Connectable conductor cross section solid-core
2.5 - 50 mm²

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-plht_4p](#)
File
(Web)

edz files

- [DA-CE-ETN.PLHT-063_4](#)
File
(Web)

Step files

- [DA-CS-plht_4p](#)
File
(Web)

Product photo



sg43611
Photo
Miniature circuit breaker (MCB)

Instruction Leaflet

- [Add-on Residual Current Protection Unit PB-HT \(IL019151ZU\)](#)
Asset
MA150501247
(PDF, 06/2020, Language independent)

Declaration of Conformity

EU

- [DA-DC-03_FLH_180820](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

