
## nVent CADDY Cat 425 Adjustable Cable Support with Flange Clip - CAT425912SM (181640)



- Requires only a hammer to install
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- Simple unlocking and locking of bar allows for additional cables to be added easily after installation
- Adjustable strap allows for multiple support sizes to reduce inventory
- Cost effective alternative to expensive cable tray
- cULus® Listed and complies with NEC® and TIA requirements for structured cabling systems
- Suitable for air handling spaces (plenum)





Part Number	CAT425912SM
Article Number	181640
Material	Steel Polyethylene Spring Steel
Finish	nVent CADDY Armour Electrogalvanized
Diameter (Ø)	100 mm 150 mm
Area	13,181 mm²
Cable Capacity, Cat 5e	425
Cable Capacity, Cat 6	325
Cable Capacity, Cat 6A	210
Flange Thickness (FT)	14.3 – 19.1 mm
Static Load (F)	450 N
Certifications	cULus



Part Number	CAT425912SM
Standard Packaging Quantity	10 pc
UPC	78285633328
EAN-13	8711893816426

NEC is a registered trademark of, and National Electrical Code (NEC) standard is a copyright of the National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are  ${\it registered\ certification\ marks\ of\ UL\ LLC}.$ 

## WARNING

nevent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved nVent, nVent CADDY, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

