



**172853**  
**DMM-125/4/I5/P-G**

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Dimensions

## DELIVERY PROGRAM

Product range  
Switch-disconnector  
Main switch  
maintenance switch

Part group reference  
DMM

Stop Function  
STOP function

with grey knob

Information about equipment supplied  
auxiliary contact fitted by user.

Notes  
in C-K5 enclosure

Number of poles  
4 pole

## Auxiliary contacts

  
0 NO

  
0 NC


Notes  
1 padlock, □ 5 mm

Locking facility  
Lockable in the 0 (Off) position

Degree of Protection  
IP65

**totally insulated**

Design  
surface mounting



Contact sequence

Switching angle  
90 °

Function

## Motor rating AC-23A, 50 - 60 Hz [P]

400 V [P]  
59 kW

Rated uninterrupted current [ $I_u$ ]  
125 A

Note on rated uninterrupted current  $I_u$   
Rated uninterrupted current  $I_u$  is specified for max.  
cross-section.

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, VDE 0660, IEC/EN 60204  
Switch-disconnector according to IEC/EN 60947-3

Certifications  
CE, RoHs, KEVA, EAC, Lloyds

Ambient temperature  
Operation [°]  
-25 - +60 °C

Ambient temperature  
Storage [°]  
-40 - +80 °C

Overvoltage category/pollution degree  
III/3

Rated impulse withstand voltage [ $U_{imp}$ ]  
6 kV

Rated insulation voltage [ $U_i$ ]  
1000 V

Mounting position  
As required

### Contacts

Mechanical variables  
Number of poles

4 pole

Mechanical variables

Auxiliary contacts

  
0 NO

Mechanical variables

Auxiliary contacts

  
0 NC

Electrical characteristics

Rated operational voltage [ $U_e$ ]

690 V AC

Electrical characteristics

Rated uninterrupted current [ $I_u$ ]

125 A

Electrical characteristics

Note on rated uninterrupted current  $I_u$

Rated uninterrupted current  $I_u$  is specified for max.  
cross-section.

Short-circuit rating

fuse

125

Short-circuit rating

Rated conditional short-circuit current [ $I_q$ ]

415 V: 30

690 V: 50 kA

Short-circuit rating

Breaking current

13.7 kA

Short-circuit rating

max. let-through energy

134 kA<sup>2</sup>s

Rated short-time withstand current (1 s current)

[ $I_{cw}$ ]

2500 A<sub>rms</sub>

Note on rated short-time withstand current  $I_{cw}$

Current for a time of 1 second

Heat dissipation per pole, current-dependent [ $P_{\text{vid}}$ ]  
4.9 W

## Switching capacity

Rated breaking capacity  $\cos \phi$  to IEC 60947-3  
400/415 V  
1000 A

Rated breaking capacity  $\cos \phi$  to IEC 60947-3  
500 V  
528 A

Rated breaking capacity  $\cos \phi$  to IEC 60947-3  
690 V  
336 A

Safe isolation to EN 61140  
Current heat loss per contact at  $I_e$   
4.5 W

Lifespan, mechanical [Operations]  
10000

AC  
AC-21A  
Rated operational current switch  
400 V 415 V [ $I_e$ ]  
125 A

AC  
AC-21A  
Rated operational current switch  
500 V [ $I_e$ ]  
125 A

AC  
AC-21A  
Rated operational current switch  
690 V [ $I_e$ ]  
125 A

AC  
AC-22A  
Rated operational current switch  
400 V 415 V [ $I_e$ ]  
125 A

AC  
AC-22A  
Rated operational current switch  
500 V [I<sub>e</sub>]  
125 A

AC  
AC-22A  
Rated operational current switch  
690 V [I<sub>e</sub>]  
125 A

AC  
AC-23A  
Rated operational current switch  
400 V 415 V [I<sub>e</sub>]  
125 A

AC  
AC-23A  
Rated operational current switch  
500 V [I<sub>e</sub>]  
66 A

AC  
AC-23A  
Rated operational current switch  
690 V [I<sub>e</sub>]  
42 A

AC  
AC-23A  
MOTOR rating AC-23A, 50 - 60 Hz [P]  
400 V 415 V [P]  
59 kW

AC  
AC-23A  
MOTOR rating AC-23A, 50 - 60 Hz [P]  
500 V [P]  
45 kW

AC  
AC-23A  
MOTOR rating AC-23A, 50 - 60 Hz [P]  
690 V [P]  
37 kW

## Terminal capacities

Flexible with ferrules to DIN 46228  
flexible  
6 - 70 mm<sup>2</sup>

Stripping length  
21 mm

Tightening torque for terminal screw  
7 Nm

### Technical safety parameters:

#### Notes

B10<sub>d</sub> values as per EN ISO 13849-1, table C1

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
125 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
4.9 W

Equipment heat dissipation, current-dependent  
[ $P_{vid}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+40 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
UV resistance only in connection with protective shield.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.



10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

# TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EO000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013])

Version as main switch  
Yes

Version as maintenance-/service switch  
Yes

Version as safety switch  
No

Version as emergency stop installation  
No

Version as reversing switch  
No

Number of switches  
1

Max. rated operation voltage  $U_e$  AC  
690 V

Rated operating voltage  
690 - 690 V

Rated permanent current  $I_u$   
125 A

Rated permanent current at AC-23, 400 V  
125 A

Rated permanent current at AC-21, 400 V  
125 A

Rated operation power at AC-3, 400 V  
0 kW

Rated short-time withstand current  $I_{cw}$   
2.5 kA

Rated operation power at AC-23, 400 V  
0 kW

Switching power at 400 V  
0 kW

Conditioned rated short-circuit current  $I_q$   
50 kA

Number of poles  
4

Number of auxiliary contacts as normally closed  
contact  
0

Number of auxiliary contacts as normally open  
contact  
0

Number of auxiliary contacts as change-over  
contact  
0

Motor drive optional  
No

Motor drive integrated  
No

Voltage release optional  
No

Device construction  
Complete device in housing

Suitable for ground mounting  
Yes

Suitable for front mounting 4-hole  
No

Suitable for front mounting centre  
No

Suitable for distribution board installation  
No

Suitable for intermediate mounting  
No

Colour control element  
Grey

Type of control element  
Short thumb-grip

Interlockable  
Yes

Type of electrical connection of main circuit  
Screw connection

Degree of protection (IP), front side  
IP65

Degree of protection (NEMA)  
Other

## DIMENSIONS

