



207068  
T0-1-15402/I1

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as  
per IEC/EN 61439

Technical data ETIM 7.0

Dimensions

## DELIVERY PROGRAM

Product range  
Control switches

Part group reference  
T0

Basic function  
ON-OFF switches

with black thumb grip and front plate


Contacts  
2

Degree of Protection  
IP65


totally insulated

Design

surface mounting



Contact sequence




Switching angle  
45 °

Switching performance  
maintained  
With 0 (Off) position

Design number  
15402

Front plate no.



FS 415

front plate  
0-1

**Motor rating AC-23A, 50 - 60 Hz [P]**

400 V [P]  
5.5 kW

Rated uninterrupted current [ $I_u$ ]  
20 A

Note on rated uninterrupted current  $I_u$   
Rated uninterrupted current  $I_u$  is specified for max.  
cross-section.

Number of contact units

1 contact unit(s)

## TECHNICAL DATA

### General

#### Standards

IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3

#### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

#### Ambient temperature

Enclosed

-25 - +40 °C

#### Overvoltage category/pollution degree

III/3

#### Rated impulse withstand voltage [ $U_{imp}$ ]

6000 V AC

#### Mechanical shock resistance

15 g

#### Mounting position

As required

### Contacts

#### Electrical characteristics

Rated operational voltage [ $U_e$ ]

690 V AC

#### Electrical characteristics

Rated uninterrupted current [ $I_u$ ]

20 A

#### Electrical characteristics

Note on rated uninterrupted current  $I_u$

Rated uninterrupted current  $I_u$  is specified for max.

cross-section.

Load rating with intermittent operation, class 12  
AB 25 % DF  
 $2 \times I_e$

Load rating with intermittent operation, class 12  
AB 40 % DF  
 $1.6 \times I_e$

Load rating with intermittent operation, class 12  
AB 60 % DF  
 $1.3 \times I_e$

Short-circuit rating  
Fuse  
20 A gG/gL

Rated short-time withstand current (1 s current)  
 $[I_{cw}]$   
320 A<sub>rms</sub>

Note on rated short-time withstand current  $I_{cw}$   
Current for a time of 1 second

Rated conditional short-circuit current  $[I_k]$   
6 kA

## Switching capacity

$\cos \phi$  rated making capacity as per IEC 60947-3  
130 A

Rated breaking capacity  $\cos \phi$  to IEC 60947-3  
230 V  
100 A

Rated breaking capacity  $\cos \phi$  to IEC 60947-3  
400/415 V  
110 A

Rated breaking capacity  $\cos \phi$  to IEC 60947-3  
500 V  
80 A

Rated breaking capacity  $\cos \phi$  to IEC 60947-3

690 V  
60 A

Safe isolation to EN61140  
between the contacts  
440 V AC

Safe isolation to EN61140  
Current heat loss per contact at  $I_e$   
0.6 W

Safe isolation to EN61140  
Current heat loss per auxiliary circuit at  $I_e$  (AC-  
15/230 V)  
0.6 CO

Lifespan, mechanical [Operations]  
> 0.4 x 10<sup>6</sup>

Maximum operating frequency [Operations/h]  
1200

AC  
AC-3  
Rating, motor load switch [P]  
220 V 230 V [P]  
3 kW

AC  
AC-3  
Rating, motor load switch [P]  
230 V Star-delta [P]  
5.5 kW

AC  
AC-3  
Rating, motor load switch [P]  
400 V 415 V [P]  
5.5 kW

AC  
AC-3  
Rating, motor load switch [P]  
400 V Star-delta [P]  
7.5 kW

AC  
AC-3  
Rating, motor load switch [P]  
500 V [P]

5.5 kW

AC  
AC-3  
Rating, motor load switch [P]  
500 V Star-delta [P]  
7.5 kW

AC  
AC-3  
Rating, motor load switch [P]  
690 V [P]  
4 kW

AC  
AC-3  
Rating, motor load switch [P]  
690 V Star-delta [P]  
5.5 kW

AC  
AC-3  
Rated operational current motor load switch  
230 V [ $I_e$ ]  
11.5 A

AC  
AC-3  
Rated operational current motor load switch  
230 V star-delta [ $I_e$ ]  
20 A

AC  
AC-3  
Rated operational current motor load switch  
400V 415 V [ $I_e$ ]  
11.5 A

AC  
AC-3  
Rated operational current motor load switch  
400 V star-delta [ $I_e$ ]  
20 A

AC  
AC-3  
Rated operational current motor load switch  
500 V [ $I_e$ ]  
9 A

AC  
AC-3

Rated operational current motor load switch  
500 V star-delta [ $I_e$ ]  
15.6 A

AC  
AC-3  
Rated operational current motor load switch  
690 V [ $I_e$ ]  
4.9 A

AC  
AC-3  
Rated operational current motor load switch  
690 V star-delta [ $I_e$ ]  
8.5 A

AC  
AC-23A  
Motor rating AC-23A, 50 - 60 Hz [P]  
230 V [P]  
3 kW

AC  
AC-23A  
Motor rating AC-23A, 50 - 60 Hz [P]  
400 V 415 V [P]  
5.5 kW

AC  
AC-23A  
Motor rating AC-23A, 50 - 60 Hz [P]  
500 V [P]  
7.5 kW

AC  
AC-23A  
Motor rating AC-23A, 50 - 60 Hz [P]  
690 V [P]  
5.5 kW

AC  
AC-23A  
Rated operational current motor load switch  
230 V [ $I_e$ ]  
13.3 A

AC  
AC-23A  
Rated operational current motor load switch  
400 V 415 V [ $I_e$ ]  
13.3 A

AC  
AC-23A  
Rated operational current motor load switch  
500 V [ $I_e$ ]  
13.3 A

AC  
AC-23A  
Rated operational current motor load switch  
690 V [ $I_e$ ]  
7.6 A

DC  
DC-1, Load-break switches L/R = 1 ms  
Rated operational current [ $I_e$ ]  
10 A

DC  
DC-1, Load-break switches L/R = 1 ms  
Voltage per contact pair in series  
60 V

DC  
DC-21A [ $I_e$ ]  
Rated operational current [ $I_e$ ]  
1 A

DC  
DC-21A [ $I_e$ ]  
Contacts  
1 Quantity

DC  
DC-23A, motor load switch L/R = 15 ms  
24 V  
Rated operational current [ $I_e$ ]  
10 A

DC  
DC-23A, motor load switch L/R = 15 ms  
24 V  
Contacts  
1 Quantity

DC  
DC-23A, motor load switch L/R = 15 ms  
48 V  
Rated operational current [ $I_e$ ]  
10 A

DC



DC-23A, motor load switch L/R = 15 ms  
48 V  
Contacts  
2 Quantity

DC  
DC-23A, motor load switch L/R = 15 ms  
60 V  
Rated operational current [ $I_e$ ]  
10 A

DC  
DC-23A, motor load switch L/R = 15 ms  
60 V  
Contacts  
3 Quantity

DC  
DC-23A, motor load switch L/R = 15 ms  
120 V  
Rated operational current [ $I_e$ ]  
5 A

DC  
DC-23A, motor load switch L/R = 15 ms  
120 V  
Contacts  
3 Quantity

DC  
DC-23A, motor load switch L/R = 15 ms  
240 V  
Rated operational current [ $I_e$ ]  
5 A

DC  
DC-23A, motor load switch L/R = 15 ms  
240 V  
Contacts  
5 Quantity

DC  
DC-13, Control switches L/R = 50 ms  
Rated operational current [ $I_e$ ]  
10 A

DC  
DC-13, Control switches L/R = 50 ms  
Voltage per contact pair in series  
32 V

Control circuit reliability at 24 V DC, 10 mA [Fault

probability]  
< 10<sup>-5</sup>, < 1 failure in 100,000 switching operations  
H<sub>f</sub>

### Terminal capacities

Solid or stranded  
1 x (1 - 2,5)  
2 x (1 - 2,5) mm<sup>2</sup>

Flexible with ferrules to DIN 46228  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Terminal screw  
M3.5

Tightening torque for terminal screw  
1 Nm

### Technical safety parameters:

#### Notes

B10<sub>d</sub> values as per EN ISO 13849-1, table C1

### Rating data for approved types

Terminal capacity  
Terminal screw  
M3.5

Terminal capacity  
Tightening torque  
8.83 lb-in

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [I<sub>n</sub>]  
20 A

Heat dissipation per pole, current-dependent [ $P_{\text{vd}}$ ]  
0.6 W

Equipment heat dissipation, current-dependent  
[ $P_{\text{vd}}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{\text{vs}}$ ]  
0 W

Heat dissipation capacity [ $P_{\text{diss}}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+40 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of  
enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating  
materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating  
materials to abnormal heat and fire due to internal  
electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
UV resistance only in connection with protective  
shield.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Control switch (EC002611)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Control switch (ec1@ss10.0.1-27-37-14-14 [ACN998011])

Type of switch  
On/Off switch

Number of poles  
2

Max. rated operation voltage  $U_e$  AC  
690 V

Rated permanent current  $I_u$   
20 A

Number of switch positions  
2

With 0 (off) position

Yes

With retraction in 0-position

No

Device construction

Surface mounted device

Width in number of modular spacings

0

Suitable for ground mounting

Yes

Suitable for front mounting 4-hole

No

Suitable for distribution board installation

No

Suitable for intermediate mounting

No

Complete device in housing

Yes

Type of control element

Toggle

Front shield size

48x48 mm

Degree of protection (IP), front side

IP65

Degree of protection (NEVA), front side

Other

## DIMENSIONS

Drilling dimensions base

